



## DK6000 data cable U/UTP Cat 6 Dca LSFH 23AWG

Category-6 and Dca Euroclass data cable, U/UTP type (Unfoiled), with copper conductor and LSFH sheath (Low Smoke Free of Halogen). It is recommended for installations where network certification is required.

It achieves a bandwidth up to 400 MHz (higher than the 250 MHz specified by the standard).

<b>Ref.</b>	2123
<b>Logical ref.</b>	CAT6L305VD
<b>EAN13</b>	8424450140789

### Other features

<b>Colour</b>	Violet
<b>Length</b>	305.00 m

### Packaging info

<b>Box</b>	305 m
<b>Pallet</b>	7320 m

### Physical data

<b>Net weight</b>	37.00 g
<b>Gross weight</b>	40.00 g
<b>Width</b>	6.00 mm
<b>Height</b>	1,000.00 mm
<b>Depth</b>	6.00 mm
<b>Main product weight</b>	37.00 g

### Highlights

- U/UTP Unfoiled UTP Cable
- Solid copper inner conductor (23AWG)

- Compatible with PoE/PoE+ (Power over Ethernet) technology, allowing the cable to power network devices
- PE (Polyethylene) copper conductor insulation, 1.02mm diameter
- LSFH (Low Smoke Free of Halogen) outer sheath, 0.50mm thick and 6.2mm diameter
- 72% nominal speed
- Certified according to the applicable standards as defined in the available declarations of conformity and performance
- Tested and approved by the Intertek (ETL Verified Mark) laboratory according to the available certification

## Discover

---

### Category 6

Data cable category Cat 6 complies with the standard for Gigabit Ethernet and it is backwards compatible, with the standards of the inferior categories (Cat 5/5e and Cat 3). Category 6 evolves over category 5E, allowing to achieve transmission frequencies of up to 250 MHz (in each pair) and 1 Gbps of throughput. It includes characteristics and specifications to avoid crosstalk and noise. This type of data cable can be used in 10BASE-T, 100BASE-T and 1000BASE-T (Gigabit Ethernet) compliant systems.

Our category 6 cables are characterized:

- Comply with TIA/EIA-568B.2-1
- Crucifix type padding
- Transfer rate up to 1Gbps
- Frequency range of up to 250 MHz and up to 400MHz in some references
- Includes rip cord to make it easier to strip the cable
- Nominal impedance of 100 ohms
- Maximum resistance per conductor below 9.38 ohms/100m

## Compatibility of RJ45 connectors with Televes data cables:

Reference	219602	219701	219901	219910	212201	2123	212302	212305	212310	212101	219302	219312	219313	219322	
Female connectors	209901/209907	OK	OK	OK	OK	OK	OK	OK	OK	OK	X	X	X	X	X
	209905	OK	OK	OK	OK	OK	OK	OK	OK	OK	X	X	X	X	X
	209921/209925	OK	OK	OK	OK	OK	OK	OK	OK	OK	X	X	OK	OK	X
	209926	OK	OK	OK	OK	OK	OK	OK	OK	OK	X	X	OK	OK	X
	209903	OK*	OK*	OK	OK*	OK*	OK*	OK*	OK*	OK*	OK	X	X	X	X
	209923	OK*	OK*	OK	OK*	OK*	OK*	OK*	OK*	OK*	OK	OK	OK*	OK*	OK
	209929/209501	OK*	OK*	OK	OK*	OK*	OK*	OK*	OK*	OK*	OK	OK	OK*	OK*	OK
Male connectors	209902	OK	OK	OK	OK	OK	OK	OK	OK	OK	X	X	X	X	X
	209961/209962	OK	OK	OK	OK	OK	OK	OK	OK	OK	X	X	X	X	X
	209904	OK*	OK*	OK	OK*	OK*	OK*	OK*	OK*	OK*	OK	X	X	X	X
	209906	OK	OK	OK	OK	OK	OK	OK	OK	OK	X	X	X	X	X
	209965/209966	OK	OK	OK	OK	OK	OK	OK	OK	OK	X	X	X	X	X
	209922	OK*	OK*	OK	OK*	OK*	OK*	OK*	OK*	OK*	X	X	OK	OK	X
	209924	OK*	OK*	OK	OK*	OK*	OK*	OK*	OK*	OK*	OK*	OK	OK*	OK*	OK

OK Compatible

OK\* Compatible, but there are better choices

X Incompatible

\*\* Mechanical compatibility

## Mounting details

### DETAIL VIEW OF THE DATA CABLE SECTION

- A. □ Inner conductor □
- B. □ Inner conductor isolation □
- C. □ Crucifix Filler □
- D. □ Outer sheath □
- E. □ Rip cord □



## Technical specifications : Ref. 2123

<b>Model</b>																				DK6000
<b>Type</b>																				U/UTP
<b>Euroclass</b>																				Dca
<b>Euroclass: Smoke Production</b>																				s2
<b>Euroclass: Flaming droplets</b>																				d2
<b>Euroclass: Acidity</b>																				a1
<b>Categorie</b>																				Cat 6
<b>Transmission bandwidth</b>																				400MHz
<b>Transfer rate</b>																				1Gbps
<b>Conductor Diameter</b>	mm																			0.55
<b>Conductor Material</b>																				Solid copper
<b>Conductor type AWG</b>																				23
<b>Conductor isolation Diameter</b>	mm																			1.02
<b>Conductor isolation Material</b>																				Polyethylene
<b>Crucifix filler</b>																				Yes
<b>Outer sheath Diameter</b>	mm																			6.2
<b>Outer sheath Material</b>																				LSFH
<b>Outer sheath Thickness</b>	mm																			0.5
<b>Rip cord</b>																				Yes
<b>Spark Test</b>	Vac																			3000
<b>Nominal impedance</b>	Ω																			100
<b>Conductor resistance</b>	Ohm/100m																			< 9.38
<b>Nominal speed</b>	%																			72
<b>Working voltage</b>	V																			300
<b>Operating temperature</b>	°C																			-25 ... 70
<b>Frequencies</b>		1 MHz	4 MHz	8 MHz	10 MHz	16 MHz	20 MHz	25 MHz	31.25 MHz	62.5 MHz	100 MHz	200 MHz	250 MHz	300 MHz	400 MHz					
<b>Attenuation (max.)</b>	dB/100m	2	3.8	5.3	6	7.6	8.5	9.5	10.7	15.4	19.8	29	32.8	--	--					
<b>Attenuation (typ.)</b>	dB/100m	1.7	3.5	5	5.6	7.1	8	8.9	10	14.4	18.3	26.2	29.4	32.8	37.7					
<b>NEXT (min.)</b>	dB/100m	74.3	65.3	60.8	59.3	56.2	54.8	53.3	51.9	47.4	44.3	39.8	38.3	--	--					
<b>NEXT (typ.)</b>	dB/100m	87.3	78.1	74.1	70.1	67.3	65.9	64.1	62.2	57.3	57	50.5	49.5	44	36.5					
<b>PS NEXT (min.)</b>	dB/100m	72.3	63.3	58.8	57.3	54.2	52.8	51.3	49.9	45.4	42.3	37.8	36.3	--	--					
<b>PS NEXT (typ.)</b>	dB/100m	84.9	76.2	71.2	67.7	64.8	64.1	62.9	60.5	56.1	52.1	46.5	45.3	41.2	35.6					
<b>ACR-N (min.)</b>	dB/100m	72.3	61.5	55.5	53.3	48.6	46.3	43.8	41.2	32	24.5	10.8	5.5	--	--					
<b>ACR-N (typ.)</b>	dB/100m	85.5	74.4	69.1	64	59.9	57.9	55.3	52.2	43	36.1	22.7	19.2	11.2	-1.2					
<b>PS ACR-N (min.)</b>	dB/100m	70.3	59.5	53.5	51.3	46.6	44.3	41.8	39.2	30	22.5	8.8	3.5	--	--					
<b>PS ACR-N (typ.)</b>	dB/100m	83.2	71.8	66.2	62	57.6	56.2	54.1	50.5	41.5	34.4	20.3	16	9	-1.7					
<b>ACR-F (min.)</b>	dB/100m	67.8	55.8	49.7	47.8	43.7	41.8	39.8	37.9	31.9	27.8	21.8	19.8	--	--					
<b>ACR-F (typ.)</b>	dB/100m	78.1	66	60.9	58.7	54.3	52.5	50.4	49	41.6	38.6	30.5	28.6	23.9	22.3					
<b>PS ACR-F (min.)</b>	dB/100m	64.8	52.8	46.7	44.8	40.7	38.8	36.8	34.9	28.9	24.8	18.8	16.8	--	--					
<b>PS ACR-F (typ.)</b>	dB/100m	74.7	63.2	58.1	56.2	52.9	50.4	48.4	46.5	40.3	35.8	28.6	26.8	20.5	16.5					
<b>Return losses (min.)</b>	dB	20	23	24.5	25	25	25	24.3	23.6	21.5	20.1	18	17.3	--	--					
<b>Return losses</b>	dB	25.6	26.6	29.3	29.8	31.9	32.3	32.1	32.5	31.6	27.7	24.8	23.1	21.8	19.3					