



## Terrestrial and satellite signal combiner 2 inputs: MATV-SAT

2-input combiner that combines a terrestrial signal with a satellite signal into a single output.

Can be used as GSM filter, thanks to the high TV-SAT rejection

Ref.	4340
EAN13	8424450043400

### Packaging info

Blister	1 pcs.
Box	6 pcs.

### Physical data

Net weight	188.00 g
Gross weight	188.00 g
Width	98.00 mm
Height	66.00 mm
Depth	27.00 mm
Main product weight	188.00 g

### Highlights

- High-screening Zamak chassis
- Current pass from the output to the SAT input, for LNB supply

### Main features

- Indoor or outdoor installation (with ref. 4163 case)
- "F" connectors

## Technical specifications : Ref. 4340

<b>Connectors</b>			"F" type	
<b>Number of inputs</b>			2	
<b>Number of outputs</b>			1	
<b>Frequency range</b>	MHz	47 ... 790		950 ... 2400
<b>IN (TERR) -&gt; OUT attenuation</b>	dB	1.5		> 30
<b>IN (TERR) -&gt; OUT A attenuation</b>	dB	1.5		> 30
<b>IN (TERR) -&gt; OUT B attenuation</b>	dB	1.5		> 30
<b>IN (SAT) -&gt; OUT attenuation</b>	dB	> 30		1.8
<b>IN (SAT A) -&gt; OUT A attenuation</b>	dB	> 30		1.8
<b>IN (SAT B) -&gt; OUT B attenuation</b>	dB	> 30		1.8
<b>Return losses (typ.)</b>	dB	> 10		> 10
<b>Operating temperature</b>	°C		-5 ... 45	
<b>Protection index (IP)</b>			23	