



## Ethernet Patch Cord S/FTP Cat 6A LSFH, grey

Preconnected Ethernet patch cord with RJ45 connector at each end. It is made of a Category-6A data cable, S/FTP type (foiled pairs and foiled cable), with a flexible copper inner conductor 26 AWG and outer sheath made of grey LSFH (Low Smoke Free of Halogen).

---

<b>Ref.</b>	209112
<b>Logical ref.</b>	PK6AL1G
<b>EAN13</b>	8424450250846

---

### Other features

---

<b>Colour</b>	Grey
<b>Length</b>	1.00 m

---

### Packaging info

---

<b>Box</b>	10 pcs.
------------	---------

---

### Physical data

---

<b>Net weight</b>	400.00 g
<b>Gross weight</b>	400.00 g
<b>Width</b>	12.00 mm
<b>Height</b>	1,010.00 mm
<b>Depth</b>	10.00 mm
<b>Main product weight</b>	44.00 g

---

### Highlights

---

- Category-6A data cable
- S/FTP Foiled FTP Cable (foiled pairs)
- Flexible copper inner conductor (26 AWG)
- Compatible with PoE/PoE+ (Power over Ethernet) technology, allowing the cable to power

network devices

- PE (Polyethylene) copper conductor insulation, 1.1 mm diameter
- Aluminium+polyester shielding foil
- Aluminium outer shielding braid
- Grey LSFH (Low Smoke Free Of Halogen) outer sheath, 0.59 mm thick and 6.2 mm diameter
- 79% nominal speed
- RJ45 connectors with gold plated connector ends with shell nickel plated

## Discover

---

### Category 6A

Data cable category Cat 6A (augmented) has its origins on Cat 6 and it is backwards compatible, with the standards of the inferior categories (Cat 6/5e and Cat 3). Category 6A evolves over category 6, allowing to achieve transmission frequencies of up to 500 MHz (in each pair) and 10 Gbps of throughput. It includes characteristics and specifications to avoid crosstalk and noise. This type of data cable can be used in 10BASE-T, 100BASE-T, 1000BASE-T and 10GBASE-T compliant systems.

Our category 6A cables are characterized for:

- Comply with TIA/EIA-568B.2-1
- Transfer rate up to 10Gbps
- Frequency range of up to 650 MHz (higher than the 500 MHz specified by the standard)
- Nominal impedance of 100 ohms
- Maximum resistance per conductor below 9.38 ohms/100m

The RJ45 is a connector commonly used in structured cable networks. With up to 8 connection pins, it is adequate both for data networks (8 pairs), as well as telephone networks (2 pairs). It is usually used in networks compliant with standards TIA/EIA-568-B.

## Technical specifications : Ref. 209112

Type		S/FTP													
Categorie		Cat 6A													
Transmission bandwidth		650MHz													
Transfer rate		10Gbps													
Conductor Diameter	mm	0.16													
Conductor Material		Flexible copper													
Conductor type AWG		26													
Conductor isolation Diameter	mm	1.1													
Conductor isolation Material		Polyethylene													
Crucifix filler		No													
Shielding foil of pairs		Aluminium + Polyester													
Outer shielding braid		Aluminium													
Outer sheath Diameter	mm	6.2													
Outer sheath Material		LSFH													
Outer sheath Thickness	mm	0.59													
Rip cord		No													
Data connector type		RJ45													
Spark Test	Vac	3000													
Nominal impedance	$\Omega$	100													
Conductor resistance	$\Omega$ /km	< 100													
Nominal speed	%	79													
Working voltage	V	300													
Operating temperature	$^{\circ}$ C	-25 ... 70													
Frequencies		1 MHz	4 MHz	8 MHz	10 MHz	16 MHz	20 MHz	25 MHz	31.25 MHz	62.5 MHz	100 MHz	200 MHz	250 MHz	500 MHz	
NEXT (typ.)	dB/100m	65	63	58.2	56.6	53.2	51.6	50	48.4	43.4	39.9	34.8	33.1	27.9	
PS NEXT (typ.)	dB/100m	62	60.5	55.6	54	50.6	49	47.3	45.7	40.6	37.1	31.9	30.2	24.8	
ACR-F (typ.)	dB/100m	63.3	51.2	45.2	43.3	39.2	37.2	35.3	33.4	27.3	23.3	17.2	15.3	9.3	
PS ACR-F (typ.)	dB/100m	60.3	48.2	42.2	40.3	36.2	34.2	32.3	30.4	24.3	20.3	14.2	12.3	6.3	
Return losses	dB	19	19	19	19	18	17.5	17	16.5	14	12	9	8	6	