Televes



RJ45 female connector Wing nut type UTP Cat 6 for data cables

RJ45 UTP Cat 6 female connector, reusable and easy to connect since no specific tools are required. The connector allows self-crimping by rotating the wing nut built into the rear part.

Supplied in 10-unit professional plastic box.

Ref.	209905
Logical ref.	CAT6BF-U
EAN13	8424450251621

Packaging info

Plastic box	10 pcs.	

Physical data

Net weight	7.00 g
Gross weight	7.00 g
Width	17.00 mm
Height	22.00 mm
Depth	31.00 mm
Main product weight	7.00 g

Highlights

• Wing nut-type connector: the rotation of the wing nut guarantees the necessary fixation and mechanical reliability

Televes

- No tools required: crimping is done by turning the wingnut with the fingers
- Reusable: can be removed and reinstalled without deteriorating or losing functionality
- Multiple-connection guaranteed without losses
- Optimal for Cat 6 UTP, Cat 5e UTP and Cat 5 UTP
- Front (180°) cable input
- Labels with connection diagrams (A or B) are included on the connector
- 50 microns gold-plated pins

Discover

What is the RJ45?

The RJ45 is a connector commonly used in structured cable networks. With up to 8 connection pins, it is adequate both for data networks (8 pairs), as well as telephone networks (2 pairs). It is usually used in networks compliant with standards TIA/EIA-568-B.

Compatibility of RJ45 connectors with Televes data cables:

Ref	erence	219602	219701	219901	219910	212201	2123	212302	212305	212310	212101	219302	219312	219313	219322
Female connectors	209901/209907	OK	OK	OK	OK	OK	OK	OK	OK	OK	Х	Х	Х	Х	Х
	209905	ОК	ОК	ОК	ОК	ОК	ОК	ОК	ОК	ОК	Х	Х	Х	Х	Х
	209921/209925	ОК	ОК	ОК	OK	ОК	OK	OK	OK	ОК	Х	Х	ОК	ОК	Х
	209926	ОК	ОК	ОК	ОК	ОК	ОК	OK	ОК	ОК	Х	Х	ОК	ОК	Х
	209903	OK*	OK*	ОК	OK*	OK*	OK*	OK*	OK*	OK*	ОК	Х	Х	Х	Х
	209923	OK*	OK*	ОК	OK*	OK*	OK*	OK*	OK*	OK*	ОК	ОК	OK*	OK*	OK
	209929/209501	OK*	OK*	ОК	OK*	OK*	OK*	OK*	OK*	OK*	ОК	ОК	OK*	OK*	OK
	209902	ОК	ОК	ОК	ОК	ОК	ОК	OK	ОК	ОК	Х	Х	Х	Х	Х
	209961/209962	ОК	ОК	ОК	ОК	ОК	ОК	OK	ОК	ОК	Х	Х	Х	Х	Х
	209904	OK*	OK*	ОК	OK*	OK*	OK*	OK*	OK*	OK*	ОК	Х	Х	Х	X
Male connectors	209906	ОК	ОК	ОК	ОК	ОК	ОК	OK	ОК	ОК	Х	Х	Х	Х	Х
	209965/209966	ОК	ОК	ОК	ОК	ОК	ОК	ОК	ОК	ОК	Х	Х	Х	Х	Х
	209922	OK*	OK*	ОК	OK*	OK*	OK*	OK*	OK*	OK*	Х	Х	ОК	ОК	Х
	209924	OK*	OK*	ОК	OK*	OK*	OK*	OK*	OK*	OK*	OK*	ОК	OK*	OK*	OK

OK Compatible
OK* Compatible, but there are better choices
X Incompatible

Televes

** Mechanical compatibility



Technical specifications: Ref. 209905

Data connector model		Female
Data connector type		RJ45
Categorie		Cat 6
Shielding type		UTP
Housing material		Polycarbonate
Voltage max.	Vac	125
Max. current	A	1.5
Contact resistance	mΩ	20
Insulation resistance	MΩ	1000
Dielectric strength (60Hz/1min)	Vac	750
Conductor type AWG		26 23
Special tool required		No
Durability (connection cycles)		750
Reusable		Yes
Cable output		180°