



Splitting Terminal Enclosure Up to 16 fibers

Designed to work as a pass-through and diverting element for optical fiber cables. Commonly used in FTTH projects, inside the buildings (usually in the secondary enclosure).

Can house up to 16 splices.

Ref.	231301
Logical ref.	OVB8
EAN13	8424450153222

Packaging info

Box	1 pcs.
------------	--------

Physical data

Net weight	730.00 g
Gross weight	730.00 g
Width	163.00 mm
Height	265.00 mm
Depth	69.00 mm
Main product weight	730.00 g

Highlights

- Built in high-resistance ABS
- Multi-fiber cable input/output of the main wiring system made by cones designed to house different fiber diameters
- Security: Door with lock, to avoid external manipulation
- Equipped with 2 independent removable trays, for up to 8 splices each

- Equipped with 2 stuffing gland at the bottom for optical fiber output. Each stuffing gland can house 4 cables of two 2 fibers each
- Includes 2 sets of stows for different splices (the first one supports 12 splices, the second 16)
- Screws for wall mounting are included
- Ingress protection code IP43 and impact protection code IK10
- Dimensions (W x H x D): 163mm x 265mm x 69mm
- Grey colour (RAL 7035)

Technical specifications : Ref. 231301

Number of fibers		16
Pre-cut openings		No
Independent compartments		No
Closure type		Door
Front door locking system		Key Lock, one-point lock
Type of connections		Fusion splice
Installation type		Wall
Protection index (IP)		43
Protection index (IK)		10
Grounding		No
Material		ABS Plastic
Colour		Grey
Height	mm	265
Width	mm	163
Depth	mm	69