



Splitting Terminal Enclosure Up to 24 fibers

Designed to work as a pass-through and diverting element for optical fiber cables. It can be used both indoors and outdoors and allows the use of up to 12 SC Simplex or LC Duplex connectors, enabling quick connectorisation, as well as the use of pre-connectorised patch cords.

Can house up to 24 splices.

Ref.	231303
Logical ref.	OVB24A
EAN13	8424450259320

Packaging info

Box	1 pcs.
------------	--------

Physical data

Net weight	1,034.00 g
Gross weight	1,132.00 g
Width	200.00 mm
Height	250.00 mm
Depth	72.00 mm

Highlights

- Built in high-resistance ABS
- Multi-fiber cable input/output of the main wiring system made by cones designed to house different fiber diameters
- Security: Door with lock, to avoid external manipulation
- White colour

- Equipped with 1 removable tray, for easier installation and handling of the fibers
- Equipped with 2 stuffing gland at the bottom for optical fiber output
- Includes several areas for fiber confinement, allowing for easy separation of backbone fibers from user connections
- Screws for wall mounting are included
- Ingress protection code IP65 and impact protection code IK08
- Dimensions (W x H x D): 205mm x 258mm x 80mm

Technical specifications : Ref. 231303

Number of fibers			24
Pre-cut openings			No
Independent compartments			No
Closure type			Door
Front door locking system			Key Lock, one-point lock
Type of connections			Connector and fusion splice
Installation type			Wall
Protection index (IP)			65
Protection index (IK)			8
Grounding			No
Material			ABS Plastic
Colour			White
Height	mm		258
Width	mm		205
Depth	mm		80