



Splitting Terminal Enclosure Up to 24 fibers

Designed to work as a pass-through and diverting element for optical fiber cables. It can be used both indoors and outdoors and allows the use of up to 12 SC Simplex or LC Duplex connectors, enabling quick connectorisation, as well as the use of pre-connectorised patch cords.

Can house up to 24 splices.

Ref.	231303
Logical ref.	OVB24A
EAN13	8424450259320

Packaging info

Box	1 pcs.
------------	--------

Physical data

Net weight	1,034.00 g
Gross weight	1,132.00 g
Width	200.00 mm
Height	250.00 mm
Depth	72.00 mm

Highlights

- Built in high-resistance ABS
- Multi-fiber cable input/output of the main wiring system made by cones designed to house different fiber diameters
- Security: Door with lock, to avoid external manipulation
- Equipped with 1 removable tray, for easier installation and handling of the fibers

- Equipped with 2 stuffing gland at the bottom for optical fiber output
- Includes several areas for fiber confinement, allowing for easy separation of backbone fibers from user connections
- Screws for wall mounting are included
- Ingress protection code IP65 and impact protection code IK08
- Dimensions (W x H x D): 205mm x 258mm x 80mm
- White colour

Technical specifications : Ref. 231303

Number of fibers		24
Pre-cut openings		No
Independent compartments		No
Closure type		Door
Front door locking system		Key Lock, one-point lock
Type of connections		Connector and fusion splice
Installation type		Wall
Protection index (IP)		65
Protection index (IK)		8
Grounding		No
Material		ABS Plastic
Colour		White
Height	mm	258
Width	mm	205
Depth	mm	80