



Splitting Terminal Enclosure Up to 8 fibers

Designed to work as a final element for optical fiber cables. Commonly used in FTTH projects, inside the buildings (usually in the secondary enclosure).

Can house up to 8 splices and 8 SC Simplex or LC Duplex adapters.

It includes 8 rubber caps for the openings, preventing the entry of dust or other elements when the connectors are not installed, keeping the inside of the enclosure clean.

Ref.	231310
Logical ref.	OSB8
EAN13	8424450174852

Packaging info

Box	1 pcs.
------------	--------

Physical data

Net weight	696.00 g
Gross weight	696.00 g
Width	210.00 mm
Height	170.00 mm
Depth	38.00 mm
Main product weight	696.00 g

Highlights

- Robust: made of steel.
- Multi-fiber input through a PG9 stuffing gland

- Possibility of installation without connectors: By perforating the caps for the passage of the fiber, keeping the gap sealed
- Equipped with a support that can house up to 8 splices
- Including 8 heat-shrink protective sleeves for the fusions and 8 fixing flanges for the correct arrangement inside the register
- Door with locking screw (manually operated)
- Screws for wall mounting are included
- Dimensions (W x H x D): 210mm x 170mm x 38mm
- Grey colour (RAL 7035)

Technical specifications : Ref. 231310

Number of fibers			8
Number of tube inlets			1.0000
Pre-cut openings			No
Independent compartments			No
Closure type			Door
Front door locking system			Screw
Type of connections			Connector and fusion splice
Installation type			Wall
Grounding			No
Material			Steel
Colour			Grey
Height	mm		170
Width	mm		210
Depth	mm		38