



Pigtail patch cord SC/APC, Single-mode (SM), LSFH indoor

Single-mode (MM) fibre optic patch cord, used for interconnecting optical equipment, have its end pre-terminated with SC/APC connectors.

The 900µm cover is of LSFH type and is recommended for indoor use. Additionally, its pre-terminated end has a short boot, facilitating installation in wall sockets, avoiding increases in attenuation due to undesirable bends, allowing the sliding of the patch cord through conduits, reducing the space required for connection, and being less demanding regarding bend radius.

Ref.	232603
Logical ref.	OSCAPC1
EAN13	8424450259306

Other features

Colour	White
Supply method	Multiple packing (25 units)
Length	1.00 m

Packaging info

Box	25 pcs.
------------	---------

Physical data

Net weight	4.00 g
Gross weight	8.00 g
Width	9.00 mm
Height	1,120.00 mm
Depth	8.00 mm
Main product weight	4.00 g

Highlights

- ITU-T G.657.A2 fiber type
- LSFH sheath, white colour
- SC/APC connectors
- 1m long

Technical specifications : Ref. 232603

Fiber core type		Single-mode (ITU-T-G.657A2)
Optical fiber type category		OS1
Fiber core diameter	μm	9
Fiber cladding diameter	μm	125
Cable structure		Tight buffer
Outer sheath Diameter	μm	900
Outer sheath Material		LSFH
Attenuation 1310nm Max	dB/km	0.5
Attenuation 1490nm Max	dB/km	0.5
Attenuation 1550nm Max	dB/km	0.5
Insertion losses Max	dB	0.5
Return losses Min	dB	60
Optical connector type		SC
Polishing type (Optical connector)		APC
Operating temperature	°C	-20 ... 70