



Optical fiber patch cord LC/APC – SC/APC, Single-mode (SM), LSFH indoor

Single-mode (SM) optical fiber patch cord, Pre-terminated on one end with an LC/APC connector and with an SC/APC connector on the other; it can thus be used as an adapter for devices with different connectorization. The sheath being LSFH, it is recommended for indoor use.

It has an end with a short boot that facilitates installation in wall sockets, avoiding attenuation increases due to undesired bending. In addition, the short boot facilitates the sliding of the patch cord through the conduits, reduces the space required for connection and the bending radius is less demanding.

Ref.	232628
Logical ref.	OSK2LCSC
EAN13	8424450279427

Other features

Colour	Orange
Supply method	Single packing
Length	2.00 m

Packaging info

Physical data

Net weight	16.00 g
Gross weight	20.00 g
Width	3.00 mm
Height	2,000.00 mm
Depth	3.00 mm
Main product weight	16.00 g

Bag	1 pcs.
------------	--------

Highlights

- ITU-T G.657.A2 fiber type
- LSFH sheath, orange colour
- LC/APC and SC/APC connectors
- 2m long

Technical specifications : Ref. 232628

Fiber core type		Single-mode (ITU-T-G.657A2)
Fiber core diameter	µm	9
Fiber cladding diameter	µm	125
Coating buffer diameter	µm	250
Outer sheath Diameter	mm	3
Outer sheath Material		LSFH
Blocking jelly		No
Attenuation 1310nm	dB/km	< 0,5
Attenuation 1550nm	dB/km	< 0,5
Insertion losses in connector 1	dB	< 0,5
Insertion losses in connector 2	dB	< 0,5
Return losses in connector 1	dB	> 60
Return losses in connector 2	dB	> 60
Optical connector type 1		LC
Polishing type (Optical connector 1)		APC
Optical connector type 2		SC
Polishing type (Optical connector 2)		APC
Short tension	N	450
Long tension	N	200
Structure reinforcement element		Aramid fibers
Short crush (@100mm)	N	500
Long crush (@100mm)	N	100
Minimum bending radius	mm	15
Operating temperature	°C	-20 ... 70