



## SC/APC 2W optical splitter 1260...1650nm 4dB

2-way splitter with SC/APC connectors for optical signals in the 1260 nm-to-1650 nm range. Specially designed to complement the Overlight series. Also recommended for applications with WideBand LNB, with optical fiber or GPON networks. The compact frame is perfect for individual installations.

<b>Ref.</b>	233710
<b>Logical ref.</b>	OV20
<b>EAN13</b>	8424450255681

### Packaging info

<b>Box</b>	1 pcs.
<b>Carton</b>	10 pcs.

### Physical data

<b>Net weight</b>	101.00 g
<b>Gross weight</b>	129.00 g
<b>Width</b>	119.00 mm
<b>Height</b>	94.00 mm
<b>Depth</b>	34.00 mm
<b>Main product weight</b>	101.00 g

### Highlights

- Low insertion losses
- High reliability
- High uniformity among outputs

- Designed for indoor installation
- 100% European design, quality, and manufacturing
- Made of robust ABS plastic
- White color (RAL 9003)
- Single-mode fiber (SM)
- SC/APC connectors

## Technical specifications : Ref. 233710

Number of outputs		2
Optical connectors Input		SC/APC
Optical connectors Output		SC/APC
Fiber type		Single-Mode
Coupling ratio (per output)		Symmetrical
Wavelength	nm	1260 ... 1650
Insertion losses	dB	< 4,1
Return losses	dB	> 60
Uniformity	dB	< 0,6
Polarization loss (PDL)	dB	< 0,3
Directivity	dB	> 55
Operating temperature	°C	-40 ... 85