



## PLC SC/APC 2D optical splitter 1260...1650 nm 4 dB

2-way PLC splitter with SC/APC connectors for optical signals in the 1260 nm-to-1650 nm range. Perfect for mounting in boxes or rack trays.

---

<b>Ref.</b>	233750
<b>Logical ref.</b>	OV2
<b>EAN13</b>	8424450184929

---

### Packaging info

---

<b>Box</b>	1 pcs.
------------	--------

---

### Physical data

---

<b>Net weight</b>	118.00 g
<b>Gross weight</b>	118.00 g
<b>Width</b>	9.00 mm
<b>Height</b>	38.00 mm
<b>Depth</b>	8.00 mm

---

### Highlights

---

- High reliability
- High uniformity among outputs
- Inside installation of boxes, trays and fiber accessories
- Low insertion losses
- Made in 900 µm single-mode fiber (SM)
- SC/APC connectors

## Technical specifications : Ref. 233750

Number of outputs		2
Optical connectors Input		SC/APC
Optical connectors Output		SC/APC
Fiber type		Single-Mode
Coupling ratio (per output)		Symmetrical
Wavelength	nm	1260 ... 1650
Insertion losses	dB	< 4,1
Return losses	dB	> 60
Uniformity	dB	< 0,6
Polarization loss (PDL)	dB	< 0,3
Directivity	dB	> 55
Operating temperature	°C	-40 ... 85
Fiber length Input	m	0,5
Fiber length Output	m	0,5