



## Angled mast: 1 m x Ø 50 mm Hot-Dip Galvanizing

Hot-Dip Galvanizing steel angled mast, extremely resistant to corrosion. 1 m long, and 300 mm high. The 50 mm diameter (Ø 50 mm) makes it perfect for mounting with V-type supports.

<b>Ref.</b>	243810
<b>Logical ref.</b>	A10030W
<b>EAN13</b>	8424450168943

### Other features

<b>Colour</b>	Grey
---------------	------

### Packing

<b>Unit</b>	1 pcs.
<b>Box</b>	25 pcs.
<b>Carton</b>	250 pcs.

### Physical data

<b>Photo with dimensions</b>	2.00
<b>Net weight</b>	2,981.00 g
<b>Gross weight</b>	2,981.00 g
<b>Width</b>	1,070.00 mm
<b>Height</b>	310.00 mm
<b>Depth</b>	50.00 mm
<b>Main product weight</b>	2,980.00 g

### Highlights

- Hot-Dip Galvanizing treatment: the best resistance to corrosion

## Main features

---

- The tube is equipped with a black cap to prevent water from accumulating inside.

## Technical specifications : Ref. 243810

Mast model		Under-roof mast
Mast material		Steel
Surface protection		Hot-dip galvanized
Length	m	1
Diameter	mm	50