



Elbowed PROEasyF IEC connector with class A+ shielded Universal: Ø 5...7.5 mm

Professional IEC connector equipped with the PRO EasyF mounting system that allows cable fixing by simply tightening a screw. Furthermore, the system makes it compatible with a wide range of coaxial cable diameters (Ø 5...7.5 mm),

Provides an extremely high shielded, thanks to its Zamak manufacturing with extra metallic foil (class A+).

Ref.	437601
EAN13	8424450133712

Other features

Connection type	Male+Female
------------------------	-------------

Packaging info

Bag	1 pcs.
Bag	10 pcs.

Physical data

Net weight	70.00 g
Gross weight	70.00 g
Width	31.00 mm
Height	32.00 mm
Depth	19.00 mm
Main product weight	36.00 g

Highlights

- Outstanding shielded: Class A+
- Compatible with a wide range of coaxial cable diameters
- Very simple installation in terms of the cable: reusable
- Simple, yet reliable and safe installation

Main features

- Elbow format
- No tools required for installation

Discover

Professional EasyF connectors

The new PROEasyF connectors guarantees A+ shielding and it eases the connection thanks to a single clamping screw that ensures a pressure on the inner conductor much more effective than the connection provided by the fitting of compression connectors.

Made of Zamak-5 with zinc coating, it provides an extraordinary durability, as proven by countless installations where PRO connectors from previous generations were used.

The contribution of the coaxial cable characteristics to the installation will depend on the quality of the connector and its mounting.

Using a high-shielding cable is not enough, if the connector does not measure up.

EasyF connectors are the most effective and efficient in the market.

One of the best advantages of the EasyF connector is the fast connection.

Furthermore, no special tools are required to achieve a higher level of shielding than the one provided by compression connectors.

The advantages at a glance

Easy and quick mounting:

- Single securing screw

- Always visible connection
- Without male unions
- Without removable parts

Secure connection:

- Its use saves installation time and cost
- Ensures the connection is reliable and there is no need for further revisions
- The installer will feel that in case of failure it would not be connector related

Electrically perfect:

- Fully automated manufacturing
- Full shielding that avoids undesirable effects on DTT reception
- Perfect adaptation to the distribution network equipment
- The perfect connector to use with the Digital Dividend thanks to its performance and quality

The professional connector

- Convenient: hinged lid and lid captive screw
- Easy: the cable inner conductor is guided through a slot in a plastic stop
- Secure: jagged rows ensure the perfect clamping of the cable sheath
- Simple: a single screw to clamp the whole set
- Class A+: extra shielding foil
- Compact: no free parts to be stored while the connection is carried out
- Made of Zamak: processed using zinc coating, double chromium plating, and RCP

Technical specifications : Ref. 437601

Connector type		CEI
Connection type		Male+Female
Coudé		Yes
Connector mounting method		EasyF
Compatibility with coaxial cables		RG-6
Nominal impedance	Ω	75