



Patch panel for Rack 19" 1RU, with 24 "RJ45" Cat 6 UTP female connectors

Designed as 1RU, it contains 24 RJ45 Cat 6 UTP female connectors for data transmission with Gigabit Ethernet standard. It allows to have a fixed distribution network on which signal can be changed just through a reconnection on the panel.

| Ref. | 533180 |
|--------------|---------------|
| Logical ref. | UAF24UTP6 |
| EAN13 | 8424450238240 |

| Packaging info | | Physical data | |
|----------------|--------|------------------------|-----------|
| Вох | 1 pcs. | Net weight | 806.00 g |
| | | Gross weight | 928.00 g |
| | | Width | 483.00 mm |
| | | Height | 44.00 mm |
| | | Depth | 92.00 mm |
| | | Main product weight | 806.00 g |

Highlights

- Strength panel: Made of high strength die-casted zinc alloy
- Port labelling included
- Reusable connectors, allowing their connectorization on several occasions without deteriorating



or losing functionality

- Designed as 1RU
- Connection table (T568A o T568B) on the panel
- Includes 4 screws and 4 nuts for installation in a 19"-rack
- Includes 2 velcro flanges and 8 plastic ties, for securing and organizing the cables
- Black colour (RAL 9005)



Technical specifications : Ref. 533180

| Number of rack units (HE) | | 1 |
|----------------------------|----|-------|
| Modular spacing (standard) | in | 19 |
| Number of connectors | | 24 |
| Data connector type | | RJ45 |
| Connector shielding | | No |
| Categorie | | Cat 6 |
| Connection type | | 110 |
| Contact resistance | mΩ | < 100 |
| Insulation resistance | MΩ | 500 |
| Return losses (typ.) | dB | 5.8 |
| Width | mm | 483 |
| Height | mm | 44 |
| Depth | mm | 95 |
| Colour | | Black |