



DIN Rail Panel for 19" Rack 3U, up to 24 single-pole positions

Designed for the installation of standard DIN rail compatible devices. It provides a common location for all peripherals that have this standardized fixing system, thus facilitating the organization in the rack.

Its main application is to house circuit breakers and differential, normal or resettable. These devices help to protect the installation against a power surge or an electrical leakage, closing the circuit and shunting the current to ground. The DIN panel has a ground cable, anchored to the chassis by means of a threaded screw, which guarantees the current shunting.

It has a removable cover for easy handling and mounting of the devices installed on the DIN rail. In addition, it includes protection profiles on the edges of the panel to prevent damage or cuts to the electrical cables, reducing the risk of accidents.

Ref.	533186
Logical ref.	UFB3DIN24
EAN13	8424450267561

Packing

Box	1 pcs.
------------	--------

Physical data

Net weight	883.00 g
Gross weight	1,027.00 g

Width	485.00 mm
--------------	-----------

Height	133.00 mm
---------------	-----------

Depth	63.00 mm
--------------	----------

Highlights

- High strength and durability: made of steel 1.5 mm thickness
- Extremely easy installation and use
- Black colour (RAL 9005)
- Designed as 3RU
- It has the capacity to accommodate up to 24 single-pole or 12 double-pole modules
- Includes 7 screws and 4 caged nuts for installation in a 19"-rack

Technical specifications : Ref. 533186

Number of rack units (HE)		3
Modular spacing (standard)	in	19
DIN rail type		35x7,5
Width	mm	485
Height	mm	133
Material		Steel
Colour		Black