## **Televes**



## Terminal Enclousure Coaxial, data, telephone and optical fiber cable

Designed to house the equipment separating the user's network from the community's. Designed to be placed in the NTE, it works as a enclosure that houses the different technologies; can be manipulated by the user.

| Ref.  | 546702        |
|-------|---------------|
| EAN13 | 8424450214435 |

#### Packaging info

#### Physical data

| Net weight   | 8,025.00 g |
|--------------|------------|
| Gross weight | 8,025.00 g |
| Width        | 640.00 mm  |
| Height       | 530.00 mm  |
| Depth        | 80.00 mm   |

#### Highlights

- Robust: made of steel.
- Pre-marked inputs for an easy opening: 16 inputs for 32mm-tube and 16 inputs for 20mm-tube
- Perforated door for better ventilation with an ABS locking tab (can be manually operated by the user)
- MDF board for product bolting (dimensions: 520x420x12mm)
- Chassis dimensions: 600 x 500 x 80mm

# **Televes**

- Frame + door dimensions: 640 x 530 x 80mm
- Equipped with a lock to avoid external manipulation
- Interchangeable door (left or right hinge)
- Chassis with lateral tabs that allow its fixing on the wall while the mortar is being applied
- Includes a ground connection between the door and the chassis
- Lacquered white (RAL 9016)



### **Technical specifications**: Ref. 546702

| Front door locking system |    | One-point lock |
|---------------------------|----|----------------|
| Installation type         |    | Wall built-in  |
| Grounding                 |    | Yes            |
| Type of ventilation       |    | No ventilation |
| Material                  |    | Steel          |
| Thickness                 | mm | 1.5            |
| Colour                    |    | White          |
| Height                    | mm | 640            |
| Width                     | mm | 530            |
| Depth                     | mm | 80.5           |