



## NevoSwitch equipped with 5 QUAD inputs and 8 outputs

When quality matters

Cascadable and quad-compatible multiswitch, equipped with 5 inputs (one terrestrial, and the four polarities of one satellite) and 8 user outputs. Can be used as a terminal (star topology) or as a cascade by using a simple switch.

Ref.	714403
Logical ref.	MS58NCQ
EAN13	8424450172865

### Other features

Power Supply	12V - 0.8A
--------------	------------

### Packaging info

Box	1 pcs.
-----	--------

### Physical data

Net weight	491.00 g
Gross weight	491.00 g
Width	137.00 mm
Height	121.00 mm
Depth	29.00 mm
Main product weight	369.00 g

### Highlights

- 12 V power supply (ref. 9916) included
- A 22 kHz tone can be generated, which makes it compatible with any LNB, including QUAD LNB.
- A switch for either powering terrestrial pre-amplifiers or allowing current circulation

- Remote power feeding using VL
- DC circulation from the inputs up
- Active terrestrial
- European design, quality, and manufacturing

## Main features

---

- Very compact
- Made of zamak
- Input and output colour identification
- Available ECO mode
- Selector switch to shift between cascade and terminal modes
- 12 V power supply
- Low power consumption

## Technical specifications : Ref. 714403

Number of inputs		5
Number of cascable outputs		5
Number of user outputs		8
Frequency range TERR.	MHz	47 ... 862
Frequency range SAT.	MHz	950 ... 2400
Input level TERR.	dBμV	92
Input level SAT.	dBμV	105
Through losses TERR.	dB	2
Through losses SAT.	dB	1.5 ... 4
Tap losses 1...8 TERR.	dB	2
Tap losses 1...8 SAT.	dB	1
Isolation H/V	dB	> 30
Isolation users	dB	> 25
Powering	Vdc	12
Max. current (PSU)	mA	40
Max. current (STB)	mA	35
Operating temperature	°C	-5 ... 45
Protection index		20