



NevoSwitch equipped with 5 QUAD inputs and 16 outputs

When quality matters

Cascadable and quad compatible multiswitch, equipped with 5 inputs (one terrestrial, and the four polarities of one satellite) and 16 user outputs. Can be used as a terminal (star topology) or as a cascade by using a simple switch.

Ref.	714415
Logical ref.	MSUK516NCQ
EAN13	8424450177884

Other features

Power Supply 12V - 1.5A (UK plug)

Packaging info

Box 1 pcs.

Physical data

Net weight 945.00 g

Gross weight 1,270.00 g

Width 137.00 mm

Height 255.00 mm

Depth 29.00 mm

Main product weight 777.00 g

Highlights

- 12 V power supply (ref. 9916) included
- A 22 kHz tone can be generated, which makes it compatible with any LNB, including QUAD LNB.
- A switch for either powering terrestrial pre-amplifiers or allowing current circulation
- Remote power feeding using VL
- DC circulation from the inputs up
- Active terrestrial
- European design, quality, and manufacturing

Main features

- Very compact
- Made of zamak
- Input and output colour identification
- Available ECO mode
- Selector switch to shift between cascade and terminal modes
- 12 V power supply
- Low power consumption

Technical specifications : Ref. 714415

Number of inputs		5
Number of cascable outputs		5
Number of user outputs		16
Frequency range TERR.	MHz	47 ... 862
Frequency range SAT.	MHz	950 ... 2400
Input level TERR.	dBµV	92
Input level SAT.	dBµV	105
Through losses TERR.	dB	4
Through losses SAT.	dB	3 ... 8
Tap losses 1...8 TERR.	dB	2
Tap losses 1...8 SAT.	dB	1
Tap losses 9...16 TERR.	dB	4
Tap losses 9...16 SAT.	dB	2
Isolation H/V	dB	> 30
Isolation users	dB	> 25
Powering	Vdc	12
Max. current (PSU)	mA	105
Max. current (STB)	mA	35
Operating temperature	°C	-5 ... 45
Protection index		20