



## NevoSwitch equipped with 5 QUAD inputs and 16 outputs

### When quality matters

Cascadable and quad compatible multiswitch, equipped with 5 inputs (one terrestrial, and the four polarities of one satellite) and 16 user outputs. Can be used as a terminal (star topology) or as a cascade by using a simple switch.

|              |               |
|--------------|---------------|
| Ref.         | 714415        |
| Logical ref. | MSUK516NCQ    |
| EAN13        | 8424450177884 |

### Other features

**Power Supply** 12V - 1.5A (UK plug)

### Packaging info

**Box** 1 pcs.

### Physical data

**Net weight** 945.00 g

**Gross weight** 1,270.00 g

**Width** 137.00 mm

**Height** 255.00 mm

**Depth** 29.00 mm

**Main product weight** 777.00 g

### Highlights

- 12 V power supply (ref. 9916) included
- A 22 kHz tone can be generated, which makes it compatible with any LNB, including QUAD LNB.
- A switch for either powering terrestrial pre-amplifiers or allowing current circulation
- Remote power feeding using VL
- DC circulation from the inputs up
- Active terrestrial
- European design, quality, and manufacturing

## Main features

---

- Very compact
- Made of zamak
- Input and output colour identification
- Available ECO mode
- Selector switch to shift between cascade and terminal modes
- 12 V power supply
- Low power consumption

## Technical specifications : Ref. 714415

|                            |      |              |
|----------------------------|------|--------------|
| Number of inputs           |      | 5            |
| Number of cascable outputs |      | 5            |
| Number of user outputs     |      | 16           |
| Frequency range TERR.      | MHz  | 47 ... 862   |
| Frequency range SAT.       | MHz  | 950 ... 2400 |
| Input level TERR.          | dBμV | 92           |
| Input level SAT.           | dBμV | 105          |
| Through losses TERR.       | dB   | 4            |
| Through losses SAT.        | dB   | 3 ... 8      |
| Tap losses 1...8 TERR.     | dB   | 2            |
| Tap losses 1...8 SAT.      | dB   | 1            |
| Tap losses 9...16 TERR.    | dB   | 4            |
| Tap losses 9...16 SAT.     | dB   | 2            |
| Isolation H/V              | dB   | > 30         |
| Isolation users            | dB   | > 25         |
| Powering                   | Vdc  | 12           |
| Max. current (PSU)         | mA   | 105          |
| Max. current (STB)         | mA   | 35           |
| Operating temperature      | °C   | -5 ... 45    |
| Protection index           |      | 20           |