

- DC circulation from the inputs up
- Active terrestrial
- European design, quality, and manufacturing

Main features

- Very compact
- Made of zamak
- Input and output colour identification
- Available ECO mode
- Selector switch to shift between cascade and terminal modes
- 12 V power supply
- Low power consumption

Technical specifications : Ref. 714416

| | | |
|----------------------------|------|--------------|
| Number of inputs | | 5 |
| Number of cascable outputs | | 5 |
| Number of user outputs | | 24 |
| Frequency range TERR. | MHz | 47 ... 862 |
| Frequency range SAT. | MHz | 950 ... 2400 |
| Input level TERR. | dBμV | 92 |
| Input level SAT. | dBμV | 105 |
| Through losses TERR. | dB | 6 |
| Through losses SAT. | dB | 4.5 ... 12 |
| Tap losses 1...8 TERR. | dB | 2 |
| Tap losses 1...8 SAT. | dB | 1 |
| Tap losses 9...16 TERR. | dB | 4 |
| Tap losses 9...16 SAT. | dB | 2 |
| Tap losses 17...24 TERR. | dB | 6 |
| Tap losses 17...24 SAT. | dB | 5 |
| Isolation H/V | dB | > 30 |
| Isolation users | dB | > 25 |
| Powering | Vdc | 12 |
| Max. current (PSU) | mA | 175 |
| Max. current (STB) | mA | 35 |
| Operating temperature | °C | -5 ... 45 |
| Protection index | | 20 |