



Televés reserves the right to modify the product

NevoSwitch 9 inputs - 32 outputs

When quality matters

Multiswitch equipped with 9 inputs (one terrestrial and 8 for two satellites, each with its four polarities) and 32 user outputs.

Can be used as a terminal (star topology) or as a cascade by using a simple switch.

Ref.	714605
Logical ref.	MS932C
EAN13	8424450173114

Packaging info

Box	1 pcs.
------------	--------

Physical data

Net weight	2,447.00 g
Gross weight	2,447.00 g
Width	206.00 mm
Height	515.00 mm
Depth	29.00 mm
Main product weight	2,435.00 g

Highlights

- 10 dB Low Gain (LG) / High Gain (HG) switch for the attenuation of the satellite input signal for each 8-user group
- Remote power feeding using VL
- Current circulation between all inputs and cascades

- Compatible with return-channel applications
- European design, quality, and manufacturing

Main features

- Very compact
- Made of zamak
- Input and output colour identification
- Available ECO mode
- Selector switch to shift between cascade and terminal modes
- 12 V power supply
- Low power consumption

Technical specifications : Ref. 714605

Number of inputs		9
Number of cascable outputs		9
Number of user outputs		32
Frequency range TERR.	MHz	88 ... 862
Frequency range SAT.	MHz	950 ... 2400
Input level TERR.	dBμV	90
Input level SAT.	dBμV	112
Through losses TERR.	dB	8
Through losses SAT.	dB	8 ... 18
Tap losses 1...8 TERR.	dB	4
Tap losses 1...8 SAT.	dB	0
Tap losses 9...16 TERR.	dB	6
Tap losses 9...16 SAT.	dB	4
Tap losses 17...24 TERR.	dB	8
Tap losses 17...24 SAT.	dB	8
Tap losses 25...32 TERR.	dB	10
Tap losses 25...32 SAT.	dB	12
Isolation H/V	dB	> 30
Isolation users	dB	> 25
Powering	Vdc	12
Max. current (PSU - LG)	mA	170
Max. current (PSU - HG)	mA	355
Max. current (STB)	mA	35
Operating temperature	°C	-5 ... 45
Protection index		20