



NevoSwitch 17 inputs - 24 outputs

When quality matters

Multiswitch equipped with 17 inputs (one terrestrial and 16 for four satellites, each with its four polarities) and 24 user outputs.

Can be used as a terminal (star topology) or as a cascade by using a simple switch.

Ref.	714804
Logical ref.	MS1724C
EAN13	8424450173268

Packaging info

Box	1 pcs.
-----	--------

Physical data

Net weight	3,328.00 g
Gross weight	3,328.00 g
Width	340.00 mm
Height	386.00 mm
Depth	30.00 mm
Main product weight	3,316.00 g

Highlights

- 10 dB Low Gain (LG) / High Gain (HG) switch for the attenuation of the satellite input signal for each 8-user group
- Remote power feeding using VL
- Current circulation between all inputs and cascades

- Compatible with return-channel applications
- European design, quality, and manufacturing

Main features

- Very compact
- Made of zamak
- Input and output colour identification
- Available ECO mode
- Selector switch to shift between cascade and terminal modes
- 12 V power supply
- Low power consumption

Technical specifications : Ref. 714804

Number of inputs		17
Number of cascable outputs		17
Number of user outputs		24
Frequency range TERR.	MHz	88 ... 862
Frequency range SAT.	MHz	950 ... 2400
Input level TERR.	dBµV	90
Input level SAT.	dBµV	112
Through losses TERR.	dB	6
Through losses SAT.	dB	6 ... 15
Tap losses 1...8 TERR.	dB	4
Tap losses 1...8 SAT.	dB	3
Tap losses 9...16 TERR.	dB	6
Tap losses 9...16 SAT.	dB	6
Tap losses 17...24 TERR.	dB	8
Tap losses 17...24 SAT.	dB	10
Isolation H/V	dB	> 30
Isolation users	dB	> 25
Powering	Vdc	12
Max. current (PSU - LG)	mA	130
Max. current (PSU - HG)	mA	260
Max. current (STB)	mA	40
Operating temperature	°C	-5 ... 45
Protection index		20