



NevoSwitch amplifier 17 inputs 27/31 dB

NevoSwitch amplifier equipped with 17 inputs (one terrestrial and the four polarities of four satellites) that allows increasing the number of users in the installation while optimizing the signal received by each of them. Around 27 dB and 31 dB amplification in terrestrial and satellite respectively. Compatible with the return path (passive).

Ref.	714809
Logical ref.	MS1727VGQ
EAN13	8424450173527

Packaging info

Box	1 pcs.
-----	--------

Physical data

Net weight	910.00 g
Gross weight	910.00 g
Width	340.00 mm
Height	121.00 mm
Depth	30.00 mm
Main product weight	902.00 g

Highlights

- Very compact
- Made of zamak
- High output level

- Switch for the selection of whether or not to power the terrestrial pre-amplifiers (VDC or OFF)
- Gain and slope individual adjustment
- Remote power feeding through all satellite trunk lines
- 12 V power supply
- Low power consumption
- Input and output colour identification

Technical specifications : Ref. 714809

Number of inputs			17
Number of outputs			17
Bands		TERR	SAT
Frequency range	MHz	88 ... 862	950 ... 2400
Output level	dBmV	52	59
Gain	dB	27	30
Gain adjustment range	dB		0 ... 20
Slope regulation	dB		0 ... 12
Isolation	dB		> 30
Powering	Vdc		12 ... 18
Max current consumption (@12V)	mA		1500
Max current consumption (@18V)	mA		950
Max. power consumption	W		18
Operating temperature	°F		23 ... 113
Protection index (IP)			20