

NevoSwitch tap 5 inputs 15dB

NevoSwitch tap equipped with 5 inputs (one terrestrial and the four polarities of one satellite), with 15 dB bridging losses, that allows the balancing of the signals received by each user.

Ref.	714902
Logical ref.	AZS515G
EAN13	8424450173411

Packaging info

Box	1 pcs.
-----	--------

Physical data

Net weight	372.00 g
Gross weight	372.00 g
Width	138.00 mm
Height	121.00 mm
Depth	29.00 mm
Main product weight	364.00 g


Highlights

- Current circulation in all inputs and all outputs with DC bypass
- Current circulation in the vertical low (VL) bypass and terrestrial output
- Low through losses

Main features

- Very compact
- Made of zamak
- Input and output colour identification
- Passive element that does not require power feeding

Application example



Technical specifications : Ref. 714902

Number of inputs		5
Number of cascable outputs		5
Number of user outputs		5
Frequency range TERR.	MHz	47 ... 862
Frequency range SAT.	MHz	950 ... 2400
Through losses TERR.	dB	1.5
Through losses SAT.	dB	1.5
Tap losses TERR.	dB	15
Tap losses SAT.	dB	17
Isolation H/V	dB	> 25
Isolation users	dB	> 25
DC pass		In□Out / Tap□In/Out
Connectors		"F" type
Operating temperature	°C	-5 ... 45
Protection index (IP)		20