



Terrestrial and satellite signal mini-combiner 2 inputs: MATV-SAT

2-input mini-combiner that combines a terrestrial signal with a satellite signal into a single output. Its innovative ultra-small size allows installation virtually anywhere, including small pattress boxes. Furthermore, miniaturization applies also to the electronics, which improve electrical behaviour and reduce impulsive noise.

Ref.	745220
Logical ref.	ESW11
EAN13	8424450186268

Packaging info

Box	10 pcs.
-----	---------

Physical data

Net weight	56.00 g
Gross weight	56.00 g
Width	57.00 mm
Height	45.00 mm
Depth	12.00 mm

Highlights

- EasyF connection system: easy to install, savings on mounting
- High-screening Zamak chassis
- Current pass from the output to the SAT input, for LNB supply

- Outstanding reliability: automated manufacturing using new generation micro-components

Main features

- Indoor or outdoor installation (with ref. 417801 case)

Technical specifications : Ref. 745220

Connectors			"F" type	
Number of inputs			2	
Number of outputs			1	
Frequency range	MHz	47 ... 790		950 ... 2400
IN (TERR) -> OUT attenuation	dB	1.5		> 30
IN (SAT) -> OUT attenuation	dB	> 35		1.5
Return losses (typ.)	dB	> 10		> 10
Operating temperature	°C		-5 ... 45	
Protection index (IP)			23	