



SFP Transceiver 1000 Base-X, 2 fibers (LC) SM

SFP (Smart Form-Factor Pluggable) transceiver module 1000 Base-X with LC connector that offers the possibility to extend the network up to 10 km through single-mode (SM) dual fiber. This high performance transceiver can be connected to an SFP input of a device to allow its access to an Ethernet signal through optical fiber.

Ref.	769210
Logical ref.	EKASFP2F
EAN13	8424450167175

Packaging info		Physical data				
Box	1 pcs.	Net weight	18.00 g 18.00 g			
Bucket	29 pcs.	Gross weight				
		Width	61.00 mm			
		Height	13.00 mm			
		Depth	12.00 mm			
		Main product	18.00 g			

weight

Highlights

- Small Form Pluggable (SFP) module
- 2 single-mode fibers (SM)
- Operating data rate of 1250 Mbps



- Duplex LC connector
- Up to 10 km transmission distance
- Differential LVPECL inputs and outputs
- TTL signal detect indicator
- Hot-pluggable capability
- CoaxData Modem (ref. 769202) compatible

Discover

What is a SFP?

The Small Form-Factor Pluggable (SFP) devices are adapters that generate an interface to allow access to an Ethernet signal through Optical Fiber. These devices can be connected to the inputs of different Ethernet and GPON equipment, allowing the transmission/reception of the information by connecting to sigle-mode or multi-mode fiber or Ethernet cables.

Among the advantages of using SFP modules, we can highlight the reduction of space, lower energy consumption, or the increase of transmission distances.

Which SFP do I need?

Based on the devices to which they are connected, the transmission speed, or the type of cable used, several options are available in the whole range of media converters. The compatibility between the SPFs and the different Ethernet and GPON equipment is described below.

Reference	769520	769210	769212	769214	769410	769411	769412	769413	769414	769415	769150
Models	ONU SFP Adapter 1000 Base-X (SC/APC)	Adaptador Ethernet – SFP 1Gb, 2 fibras (LC/UPC) SM	Kit: 2 Ethernet – SFP Adapters 1Gb, 1 fiber (LC/UPC) SM	Ethernet – SFP+ Adapter 10Gb, 2 fiber (LC/UPC)	SFP Adapter GPON B+, 1 fiber (SC/PC)	SFP Adapter 1Gb, RJ45 connector	Ethernet – SFP+ Adapter 10Gb, 2 fiber (LC/UPC)	SFP Adapter GPON C+, 1 Fiber (SC/PC)	SFP Adapter GPON C+, 1 Fiber (SC/PC)	SFP Adapter GPON B+, 1 Fiber (SC/PC)	Ethernet – SFP Adapter 1Gb, 2 fibers (LC/PC) MM




Compatible with Managed Ethernet Switches: 769140 769141 769144 769145 769145 769146 769147 769148 769149 769151 769152	ОК	ОК	ОК	ОК*	-	-	ОК*	-	-	-	ОК
Compatible with Unmanaged Ethernet Switches: 768115 768116	-	ОК	ОК	-	-	-	-	-	-	-	ОК
Compatible with Industrial Switches: 768150	ОК	ОК	ОК	-	-	-	-	-	-	-	ОК
Compatible with Routers: 769115	-	ОК	ОК	OK	-	-	-	-	-	-	ОК
Compatible with GPON OLT modules: 769403 769420 769421 769422	-	-	ОК	OK**	ОК	ОК	ОК	ОК	OK**	ОК**	ОК**
Compatible with Media Converters: 769215	-	ОК	ОК	-	-	-	-	-	-	-	ОК
Compatible with WaveData: 769002	-	ОК	ОК	-	-	-	-	-	-	-	ОК

* Compatible with Ethernet switches with SFP+ ports: 769145, 769146, 769148, 769149, 769151 or 769152.

** Compatible with OLT512EVO: 769403.

Application example







Technical specifications : Ref. 769210

Transceiver type		SFP
Fiber type		Single-Mode
Transmitter wavelength	nm	1310
Transmitter output power	dBm	-93
Optical receiver sensitivity	dBm	-19
Forwarding rate	Mb/s	1250
Transmission distance	km	< 10
Powering	Vdc	3.13 3.46
Operating temperature	°C	-20 60