



CIES Luminaire Z-Series 12LED 40W

Ecological lights made of technical polymer invulnerable everywhere

CIES is the first series of luminaires made of technical polymers specially designed by Televes, combining design, mechanical engineering and the latest electronic technology. These luminaires have a unique style that is also customisable! You can choose from a large number of alternatives: different casing colours, wide colour temperature range, different optical options, and much more.

CIES is an eco-friendly lighting option, from its production using 100% recyclable materials, in a process that minimises the carbon footprint, to its high energy efficiency and durability, which reduces waste generation. What's more, the materials are very light and at the same time resistant, which optimises all the transport, installation and maintenance tasks that are naturally linked to a public luminaire.

Thanks to this range of luminaires, an innovative and ideal solution is provided for the most aggressive environments, especially for maritime and seaside areas.

The Z series offers maximum flexibility by incorporating a standard Zhaga Book 18 connector that enables Plug&Play connection with remote management nodes and facilitates sensor integration. It also offers CLO (Constant Lumen Output) regulation, NFC programming and 5-step multi-level pre-programmed dimming.

In addition, this open interface allows the Z series to be connected to remote management systems,

combining the possibilities of full integration with additional sensors. It incorporates D4i-certified drivers and DALI2, Ready2Mains and U6Me2 communication protocols over the power line. Thus, our luminaires can be seamlessly integrated into Smart City projects project.

Ref.	60090200
------	----------

Other features

Number of LEDs	12
Lighting control	Remote control
Power	40.00 W

Packaging info

Box	1 pcs.
-----	--------

Physical data

Net weight	4,151.00 g
Gross volume	28.00 dm³
Gross weight	5,351.00 g
Width	263.00 mm
Height	250.00 mm
Depth	504.00 mm
Main product weight	4,151.00 g

Highlights

- **Resistant in any environment:** made of corrosion-resistant materials, self-formulated technical polymers and stainless steel
- **Maximum safety:** technical polymer casing (non-conductive material) and automatic electrical disconnection on opening. Class II and SELV
- **Easy installation and maintenance:** light weight and handy format with tool-free opening and locking of the top cover. Quick on-site replacement of all components
- **Eco-friendly luminaire:** produced from 100% recyclable materials, in a manufacturing process that minimises the carbon footprint. Thanks to this and to its high operating efficiency, CIES helps

to preserve the environment and respect for ecology

- **Supports the quality of the night sky:** in accordance with the IAC (Instituto de Astrofísica de Canarias) requirements, the luminaire is suitable for areas of special protection from light pollution (flux emission to the upper hemisphere < 0.1%)
- **100% made in Televes:** technology designed and manufactured in our cutting-edge facilities, guaranteeing total control, with demanding quality monitoring, over each of the production phases

Discover

Our ranges of luminaires encompass a wide range of powers and number of LEDs, in addition to being customizable in the types of lighting control, colour temperatures, optics and their light distribution, and finishes. **A product can be configured according to these parameters, and ordered by its numerical or logical reference**, as follows:

Selecting the luminaire by the numerical reference:

This is a numerical code made up of 14 digits:

- The first 6 digits represent a code that depends on the Series of the luminaire, the number of LEDs and the power
- The next 8 digits allow you to choose the configurable parameters of the luminaire: lighting control, colour temperature, type of optics and finish

Series		Dimming		Colour Temperature		Optics		Finish	
631703	Urban Alameda E 24LED 53W	00	No Dimming	18	PC Amber	02	SP	02	Black
631713	Urban Alameda E 24LED 39W	01	Dimming	22	2200K	11	D90	xx	Custom
				27	2700K	17	T2-C90		
				30	3000K	18	T3-B90		
				40	4000K				

Selecting the luminaire by logical reference:

This is an alphanumeric code composed of an unlimited number of characters, describing the

luminaire's characteristics using logical abbreviations, to facilitate its interpretation. It is divided into 2 groups of characters, separated by a hyphen:

- The first group specifies: the luminaire series, the number of LEDs, the colour temperature, and the lighting control
- The second group specifies: the type of optics, the finish and the power

An example of a logical reference: UA2418D-D90BL53

- **UA** – *Urban Alameda*
- **24** – *24 LEDs*
- **18** – *Colour Temperature: PC Amber*
- **D** – *Dimming included*
- **D90** – *D90 Optics*
- **BL** – *Black colour*
- **53** – *53W Power*

Range & LED number		Colour Temperature		Dimming		Optics	Finish		Power	
UA24	<i>Urban Alameda E 24LED</i>	18	<i>PC Amber</i>	(ø)	<i>No Dimming</i>	SP	BL	<i>Black</i>	53	<i>53W</i>
		22	<i>2200K</i>	D	<i>Dimming</i>	D90	xx	<i>Custom</i>	39	<i>39W</i>
		27	<i>2700K</i>			T2-C90				
		30	<i>3000K</i>			T3-B90				
		40	<i>4000K</i>							

Graphic documentation



Light distribution curve



Light distribution curve



Light distribution curve



Light distribution curve



Light distribution curve



Light distribution curve

Features



A luminaire with a unique personality

It combines design, engineering and modernity

CIES features a slightly wavy design, that evokes the ocean tides of the environment surrounding the natural park of the Atlantic Islands of Galicia. Created in a maritime and island environment, CIES is known for its excellent performance in extreme weather conditions.

Its design inspired by the Galician archipelago is manifested in the contrast between the strength and hardness of its materials and the

lightness and mellowness of its style, such as the fine sand dunes that harmonise with the robustness of the islands.




Invulnerable in any environment

Designed to last

CIES is made of corrosion-proof materials: technical polymers with a proprietary formula and stainless steel. By avoiding the use of mixed metals, the possibility of galvanic corrosion is completely eliminated, thus ensuring a long life for the luminaire.

Its UV-stabilised technical polymer casing is vandal-resistant, withstanding impacts of IK10 level.

CIES is the ideal luminaire for maritime areas, as it is particularly resistant to exposure to adverse weather conditions with high levels of humidity and/or salinity.



A world of possibilities

Customisable style for every situation

Each situation requires specific lighting features, that's why our luminaires offer multiple alternatives to meet the needs of each context:

- A wide selection of highly homogeneous colour temperatures (SDCM<3): PC Amber, 2,200, 2,700, 3,000 and 4,000°K
- 7 different types of optics are available to achieve lighting adapted to any environment: P, ME, T2, T3, T4, APZ and SCL
- Variety of finishes in any colour of the RAL range
- CRI>70 and available on request CRI>80 and CRI>90

And if you don't find what you are looking for, we have even more options available on request. We are pleased to study your project in a tailored, non-binding way. Contact us, and we will help you choose the perfect lighting.



Perfect thermal management

Materials and design that enhance dissipation

The CIES luminaire has a passive cooling system for the light source. High-quality thermopolymer heat sinks ensure thermal conductivity, resulting in great temperature stability.

In addition, the electronics compartment is separated from the LED modules, which prevents heat transfer between the two points.

Thanks to the thermal protection of the electronics, the light's lifetime is maximised (L90B10 > 100,000h at 25°C) and its efficiency is greatly improved (up to 160 lm/W).



Easy installation and maintenance

On-site and tool-free replacement

CIES has been designed to simplify installation and maintenance tasks as much as possible. From its light weight and handy format, to its tool-free cover opening and locking system, facilitating on-site replacement of any of its components.

Moreover, the luminaire has a self-cleaning system thanks to the grooves located in the top part of the luminaire, helping to clean and preventing possible degradation due to the accumulation of dirt.



Sustainable and ecological lighting

Supporting the quality of the night sky

Inspired by a protected natural area, CIES supports the preservation of the environment and respects the ecology and quality of the night sky. According to the requirements of the IAC (Instituto de Astrofísica de Canarias), CIES is suitable for areas of special protection against light pollution, with a light emission to the upper hemisphere of less than 0.1%, emitting an adequate luminous flux, directed only towards the areas of interest.



Environmentally friendly under the 3 R's

Reduce, re-use and recycle

In order to reduce environmental damage and take care of our planet, we take responsibility to contribute by following the 3 R rule:

- Reduce: Our manufacturing process reduces by 50% the carbon footprint generated, compared to aluminium equivalents
- Reuse: The luminaire can live on in the infrastructure, thanks to a LED module and driver replacement sustainably, supporting the circular economy
- Recycle: The luminaire is made of 100% recyclable materials




100% electrical safety

Maximum protection

This luminaire has the best levels of electrical protection: its Class II guarantees safety without the need for ground connection thanks to the double isolation of the components. Furthermore, the SELV certificate guarantees an output voltage of less than 60V, minimising the risk of electrocution in the event of system failure. In addition, its driver, optical group and IP68 connections offer integral protection to all the optical and electronic elements against the ingress of water and dust, eliminating any effect caused by external agents.

Finally, the casing made of technical polymer (non-conductive material) eliminates completely the possibility of electrocution in the event of contact with the luminaire.



Control and connectivity

Range of luminaires with Zhaga Book 18 socket and D4i certified driver

This range is equipped with D4i (Digital Illumination Interface Alliance) certified drivers, which have the ability to store luminaire data. At the same time, D4i defines how to feed from the driver to other DALI2 devices connected through the bus, simplifying communication with sensors.

All Z Series luminaires are DALI2 and CLO dimmable and include the standard Zhaga Book 18 socket, which allows Plug&Play connection with remote management nodes and the integration of multiple sensors (presence, twilight, noise, air quality...).



Televes quality guarantee


With over 60 years of European manufacturing experience

Our cutting-edge facilities are equipped with all the means to guarantee a quality and reliable luminaire, highlighting precise traceability and rigorous verification of all processes. This is possible thanks to an advanced methodology of product design under simulation and in-house manufacturing on robotised lines, in collaboration with national and local providers.

Mounting details

Quick and easy mounting by using a single accessory for vertical and horizontal position of great strength and durability, made from a specially-formulated technical polymer.

The rotation of the lighting unit can be adjusted up to 30°. It is also adaptable to posts, columns and arms with Ø 42 to 60 mm, and adapters are available for other diameters.



Indication of tilt angles for quick calibration for easy installation.



Tool-free top opening for access to electronics and LED module. Electrical disconnection on opening to minimise the risk of electrocution.



Technical specifications : Ref. 60090200

Number of leds					12				
Power	W				40				
Pre-programmed dimming					Yes				
Control interface					Dali 2				
Node/sensor connection type					1x Zhaga				
Optic type options					ME				
Lens type		P	T2	T3	PC lens	APZ	SCL	T4	
Color temperature options		PC lens	PC lens	PC lens	PC lens	PC lens	PC lens	PC lens	
Luminous flux	lm	2200K	2700K	3000K	4000K			PC Amber	
Lighting efficiency	lm/W	4540	4996	5520	5720			2340	
LED current	mA	113.5	124.9	138	143			58.5	
Duration	h	500	500	500	500			1000	
Working life					100000				
Constant light output (CLO)					L90B10				
Standard Deviation Colour Matching (SDCM)					Yes				
Color rendering index (CRI)					< 3				
CE Mark					70				
ENEC Certificate					Yes				
Protection Class IEC					No				
EU RoHS Compliant					Class II				
IK Rating (light module)					Yes				
IK Rating (whole luminaire)					10				
IP Rating (light module)					10				
IP Rating (whole luminaire)					66				
Color					66				
Material					White/Grey				
Material cover					Technical Polymer				
Fixation Material					Without cover				
Mast diameter Max	in				Technical Polymer				
Mast diameter Min	in				2.362				
Mounting method					1.654				
Surface facing the wind	m²				Post top/side entry				
Number of LED modules					0.115				
Minimum power factor					1				
Lighting source type					0.9500				
Replaceable light source					LED				
Cable					Yes				
Power consumption tolerance	%				Yes				
Lighting flux tolerance	%				5				
Electric connection					8				
Inrush current	A				3-pole waterproof connector				
Input voltage Max	Vac				26				
Input voltage Min	Vac				240				
Mains frequency					220				
Max. Operating temperature	°F				50 Hz				
Min. Operating temperature	°F				104				
					-31				