



Urban Maia Luminaire N-Series 12LED 39W

Luminaires with a fresh style to enhance lighting in the heart of cities

Decorative urban luminaire made of die-cast aluminium. The Urban Maia series has a compact design with smooth geometric lines, which integrates harmoniously with the environment, making it perfect for urban and residential spaces. Urban Maia is designed with a lateral arrangement, perfect for areas that require a specific light distribution, such as streets, avenues, housing estates... With Urban Maia, perfect visual conditions are guaranteed, maintaining the quality of the night sky, while at the same time taking care of the aesthetics of the environment thanks to its modern and elegant style.

It stands out for its easy installation and maintenance without the need of tools. In addition, its high-quality tempered glass protector favours visual comfort and reduces glare.

The N series offers maximum flexibility by adding dimming connectors under ANSI C136.41 NEMA standard, which allows a plug&play connection to remote management nodes and thus provides the ability to connect to IoT infrastructures. Furthermore, this open interface allows the N Series to be connected to any remote management system, combining the possibilities of full integration with additional sensorisation. Thus, our luminaires can be perfectly integrated into any Smart City project

| | |
|-------|---------------|
| Ref. | 63081400 |
| EAN13 | 8424450306970 |

Other features

| | |
|------------------|----------------|
| Number of LEDs | 12 |
| Lighting control | Remote control |
| Power | 39.00 W |

Packaging info

| | |
|-----|--------|
| Box | 1 pcs. |
|-----|--------|

Physical data

| | |
|--------------|------------|
| Net weight | 8,000.00 g |
| Gross weight | 9,700.00 g |
| Width | 519.00 mm |
| Height | 192.00 mm |
| Depth | 617.00 mm |

Highlights

- **Design and quality:** die-cast aluminium body with high quality tempered glass closure and compact and stylish design with geometric lines
- **100% electrical safety:** Class II with no need for grounding and SELV certified
- **Quick and tool-free maintenance:** with electrical disconnection on opening
- **Energy saving:** long maintenance-free service life, which increases savings compared to other technologies, achieving savings of up to 80%
- **Supports the quality of the night sky:** in accordance with the IAC (Instituto de Astrofísica de Canarias) requirements, the luminaire is suitable for areas of special protection against light pollution (flux emission to the upper hemisphere < 0.1%)
- **Quality guarantee:** technology designed and manufactured in our state-of-the-art facilities, in collaboration with national and local providers, ensuring total control, with accurate traceability and rigorous verification of all processes

Discover

Our ranges of luminaires encompass a wide range of powers and number of LEDs, in addition to being customizable in the types of lighting control, colour temperatures, optics and their light distribution, and finishes. **A product can be configured according to these parameters, and ordered by its numerical or logical reference**, as follows:

Selecting the luminaire by the numerical reference:

This is a numerical code made up of 14 digits:

- The first 6 digits represent a code that depends on the Series of the luminaire, the number of LEDs and the power
- The next 8 digits allow you to choose the configurable parameters of the luminaire: lighting control, colour temperature, type of optics and finish

| Series | | Dimming | | Colour Temperature | | Optics | | Finish | |
|---------------|----------------------------------|-----------|-------------------|--------------------|-----------------|-----------|---------------|-----------|---------------|
| 631703 | <i>Urban Alameda E 24LED 53W</i> | 00 | <i>No Dimming</i> | 18 | <i>PC Amber</i> | 02 | <i>SP</i> | 02 | <i>Black</i> |
| 631713 | <i>Urban Alameda E 24LED 39W</i> | 01 | <i>Dimming</i> | 22 | <i>2200K</i> | 11 | <i>D90</i> | xx | <i>Custom</i> |
| | | | | 27 | <i>2700K</i> | 17 | <i>T2-C90</i> | | |
| | | | | 30 | <i>3000K</i> | 18 | <i>T3-B90</i> | | |
| | | | | 40 | <i>4000K</i> | | | | |

Selecting the luminaire by logical reference:

This is an alphanumeric code composed of an unlimited number of characters, describing the luminaire's characteristics using logical abbreviations, to facilitate its interpretation. It is divided into 2 groups of characters, separated by a hyphen:

- The first group specifies: the luminaire series, the number of LEDs, the colour temperature, and the lighting control
- The second group specifies: the type of optics, the finish and the power

An example of a logical reference: UA2418D-D90BL53


- **UA** – *Urban Alameda*
- **24** – *24 LEDs*
- **18** – *Colour Temperature: PC Amber*

- **D** – Dimming included
- **D90** – D90 Optics
- **BL** – Black colour
- **53** – 53W Power

| Range & LED number | | Colour Temperature | | Dimming | | Optics | Finish | | Power | |
|--------------------|------------------------------|--------------------|-----------------|----------|-------------------|---------------|-----------|---------------|-----------|------------|
| UA24 | <i>Urban Alameda E 24LED</i> | 18 | <i>PC Amber</i> | (∅) | <i>No Dimming</i> | SP | BL | <i>Black</i> | 53 | <i>53W</i> |
| | | 22 | <i>2200K</i> | D | <i>Dimming</i> | D90 | xx | <i>Custom</i> | 39 | <i>39W</i> |
| | | 27 | <i>2700K</i> | | | T2-C90 | | | | |
| | | 30 | <i>3000K</i> | | | T3-B90 | | | | |
| | | 40 | <i>4000K</i> | | | | | | | |


Graphic documentation

ME




cd/klm ■ C0 - C180 ■ C90 - C270 $\eta = 88\%$
Light distribution curve

P




cd/klm ■ C0 - C180 ■ C90 - C270 $\eta = 94\%$
Light distribution curve

T2




cd/klm ■ C0 - C180 ■ C90 - C270 $\eta = 90\%$
Light distribution curve

T3



cd/klm ■ C0 - C180 ■ C90 - C270 $\eta = 92\%$
Light distribution curve


PX



cd/klm ■ C0 - C180 ■ C90 - C270 $\eta = 100\%$

Light distribution curve


SCL



cd/klm ■ C0 - C180 ■ C90 - C270 $\eta = 86\%$

Light distribution curve


APZ



cd/klm ■ C0 - C180 ■ C90 - C270 $\eta = 96\%$


Light distribution curve

T4



cd/klm ■ C0 - C180 ■ C90 - C270 $\eta = 94\%$

Light distribution curve



Features

Fresh, rust-free design that lasts over time



The Urban Maia luminaire consists of a circular die-cast aluminium body with a modern and stylish design that blends perfectly into urban and residential environments.

Its high quality tempered glass enclosure improves visual comfort and reduces glare, providing the appropriate amount of light for each situation.

On the other hand, the quality is shown in the luminaire's high durability. Thanks to the 6063 T5 aluminium heatsink, which ensures excellent thermal management of the LED modules, the luminaire's service life is extended and efficiency is improved.

Quick and tool-free maintenance



The Urban Maia series features an optimised design to allow any maintenance task to be carried out quickly and without the need of tools. The casing includes a locking system to fix the cover of the luminaire, making easier the replacement on site of its components. In addition, its light weight makes it easy to handle during installation and manipulation of the luminaire.

Maximum security



The Urban Maia luminaire has the highest levels of electrical protection: its Class II guarantees safety without the need for grounding thanks to the double isolation of the components. Furthermore, the SELV certificate provides an output voltage of less than 60V, minimising the risk of electrocution in the case of system failure. In addition, its driver, optical group and IP67 connections offer integral protection to all optical and electronic elements against water and dust ingress, eliminating any effect caused by external agents.

In addition, Urban Maia includes an automatic disconnection system, which shuts off the electric current when the luminaire is opened. This avoids the risk of electrocution when manipulating the luminaire.

A world of possibilities




Each situation requires specific lighting features, that's why our luminaires offer multiple alternatives to meet the needs of each context:

- A wide selection of highly homogeneous colour temperatures (SDCM<3): PC Amber, 2,200, 2,700, 3,000 and 4,000°K
- 9 different types of optics are available to achieve lighting adapted to any environment: P, ME, T2, T3, T4, APZ, SCL, PX and PXL
- Variety of finishes in any colour of the RAL range
- CRI>70 and available on request CRI>0 and CRI>90

And if you don't find what you are looking for, we have even more options available on request. We are pleased to study your project in a tailored, non-binding way. Contact us, and we will help you choose the perfect lighting.

Control and connectivity



N series incorporates drivers with 1-10V communication protocol, allowing luminous flux regulation between 1 and 100% by varying the voltage of the input signal from 1 to 10V. Luminaires of this series include the ANSI C136.41 NEMA standard socket that allows Plug&Play connection with remote management nodes and the integration of several sensors (presence, twilight, noise, air quality...).

Televes quality guarantee



Our cutting-edge facilities are equipped with all the means to guarantee a quality and reliable luminaire, highlighting precise traceability and rigorous verification of all processes. This is possible thanks to an advanced methodology of product design under simulation and in-house manufacturing on robotised lines, in collaboration with national and local providers.

Mounting details

Tool-free top opening for access to electronics and LED module. Electrical disconnection on opening to minimise the risk of electrocution.

Assembly is quick and easy by means of a strong, durable and unique accessory for vertical and horizontal installation. The position gradation can be adjusted up to 90°.

It is adaptable to poles, columns and arms from Ø 42 to 60 mm, adapters for other tube diameters are available.



Technical specifications : Ref. 63081400

| | | | | | | | | | | | |
|---|----------------|---------|---------|---------|---------|-----------------------------|-----------|---------|---------|----------|----------------------|
| Number of leds | | | | | | | | | | | 12 |
| Power | W | | | | | | | | | | 39 |
| Pre-programmed dimming | | | | | | | | | | | No |
| Control interface | | | | | | | | | | | 1-10V |
| Node/sensor connection type | | | | | | | | | | | 1x ANSI C136.41 Nema |
| Optic type options | | | | | | | | | | | |
| Lens type | | P | T2 | T3 | ME | APZ | PX | SCL | T4 | | |
| | | PC lens | PC lens | PC lens | PC lens | PC lens | PMMA lens | PC lens | PC lens | | |
| Color temperature options | | 2200K | | 2700K | | 3000K | | 4000K | | PC Amber | |
| Luminous flux | lm | 4173 | | 4563 | | 4758 | | 5070 | | 1950 | |
| Lighting efficiency | lm/W | 107 | | 117 | | 122 | | 130 | | 50 | |
| LED current | mA | 500 | | 500 | | 500 | | 500 | | 1000 | |
| Duration | h | | | | | 100000 | | | | | |
| Working life | | | | | | L90B10 | | | | | |
| Constant light output (CLO) | | | | | | No | | | | | |
| Standard Deviation Colour Matching (SDCM) | | | | | | < 3 | | | | | |
| Color rendering index (CRI) | | | | | | 70 | | | | | |
| CE Mark | | | | | | Yes | | | | | |
| ENEC Certificate | | | | | | No | | | | | |
| Protection Class IEC | | | | | | Class II | | | | | |
| EU RoHS Compliant | | | | | | Yes | | | | | |
| IK Rating (light module) | | | | | | 8 | | | | | |
| IK Rating (whole luminaire) | | | | | | 8 | | | | | |
| IP Rating (light module) | | | | | | 66 | | | | | |
| IP Rating (whole luminaire) | | | | | | 66 | | | | | |
| Colour | | | | | | Black | | | | | |
| Material | | | | | | Aluminium | | | | | |
| Fixation Material | | | | | | Aluminium | | | | | |
| Mounting method | | | | | | Post top/side entry | | | | | |
| Surface protection | | | | | | Powder coating | | | | | |
| Surface facing the wind | m ² | | | | | 0.211 | | | | | |
| Number of LED modules | | | | | | 1 | | | | | |
| Minimum power factor | | | | | | 0.9500 | | | | | |
| Lighting source type | | | | | | LED | | | | | |
| Replaceable light source | | | | | | Yes | | | | | |
| Cable | | | | | | Yes | | | | | |
| Power consumption tolerance | % | | | | | 5 | | | | | |
| Lighting flux tolerance | % | | | | | 8 | | | | | |
| Electric connection | | | | | | 3-pole waterproof connector | | | | | |
| Inrush current | A | | | | | 26 | | | | | |
| Input voltage Max | Vac | | | | | 240 | | | | | |
| Input voltage Min | Vac | | | | | 220 | | | | | |
| Mains frequency | | | | | | 50 Hz | | | | | |
| Max. Operating temperature | °C | | | | | 40 | | | | | |
| Min. Operating temperature | °C | | | | | -35 | | | | | |