



Launch armoured fiber for OTDR measurement multi-mode (MM) OM4 SC/PC-LC/PC, 150m

Multi-mode (MM) OM armoured launch fiber, with SC/PC connector at one end and LC/PC connector at the other end.

The leading fiber is a special fiber that is connected in front of a measurement section in an OTDR measurement. The fiber is indispensable for a standard-compliant measurement and fades out unwanted effects of the device on the measurement section. This is the only way to correctly measure the first and last connector of a link.

One of the fiber ends must be compatible with the connector of the OTDR to be used.

Ref.	230990
Logical ref.	VF-OM4SCLC-150
EAN13	8424450317051

Packaging info

Box	1 pcs.
------------	--------

Physical data

Net weight	400.00 g
Gross weight	600.00 g
Width	110.00 mm
Height	110.00 mm
Depth	50.00 mm

Main product weight	400.00 g
----------------------------	----------

Highlights

- SC/UPC and LC/UPC connectors
- Immediately ready for use: The unique opening mechanism ensures rapid deployment
- Armoured cable ends. Special protection of cable ends ensured to avoid high attenuation due to damage
- High quality fiber MM OM4-G.651.1
- Supplied in compact carrying case
- 150m length

Technical specifications : Ref. 230990

Fiber core type		Multi-mode (ITU-T-G.651.1)
Optical fiber type category		OM4
Return losses in connector 1	dB	> 50
Return losses in connector 2	dB	> 50
Optical connector type 1		SC
Polishing type (Optical connector 1)		PC
Optical connector type 2		LC
Polishing type (Optical connector 2)		PC
Operating temperature	°C	-33 ... 60