



Launch armoured fiber for OTDR measurement single-mode (SM) SC/UPC-LC/APC, 150m

Single-mode (SM) armoured launch fiber, with SC/UPC connector at one end and LC/APC connector at the other end.

The leading fiber is a special fiber that is connected in front of a measurement section in an OTDR measurement. The fiber is indispensable for a standard-compliant measurement and fades out unwanted effects of the device on the measurement section. This is the only way to correctly measure the first and last connector of a link.

One of the fiber ends must be compatible with the connector of the OTDR to be used.

Ref.	236192
Logical ref.	VF-SCLCA-150
EAN13	8424450317037

Packaging info

Box	1 pcs.
------------	--------

Physical data

Net weight	400.00 g
Gross weight	600.00 g
Width	110.00 mm
Height	100.00 mm
Depth	50.00 mm

Main product weight	400.00 g
----------------------------	----------

Highlights

- SC/UPC and LC/APC connectors
- Immediately ready for use: The unique opening mechanism ensures rapid deployment
- Armoured cable ends. Special protection of cable ends ensured to avoid high attenuation due to damage
- High quality fiber SM-G.657.A1
- Supplied in compact carrying case
- 150m length

Technical specifications : Ref. 236192

Fiber core type		Single-mode (ITU-T-G.657.A2)
Fiber core diameter	μm	9
Fiber cladding diameter	μm	125
Blocking jelly		No
Return losses in connector 1	dB	> 50
Return losses in connector 2	dB	> 60
Optical connector type 1		SC
Polishing type (Optical connector 1)		UPC
Optical connector type 2		LC
Polishing type (Optical connector 2)		APC
Operating temperature	°C	-33 ... 90