



Multioperator Enclosure Up to 48 female-female adapters, ABS

Designed to work as a distribution point for optical fiber cables. Commonly used in FTTH projects, where it simplifies the interconnection between the user's network and the operator's network. Allows the joint installation of several enclosures, while still allowing the interconnection between them. The vertically stackable design with direct intercommunication among enclosures provides the flexibility required to extend the services based on the specific needs for each installation.

Independent compartments with door and lock, separated by a panel of up to 48 SC Simplex or LC Duplex adapters.

It is made of ABS plastic, which gives it great durability and light weight. In addition, it includes 6 stackable fiber trays, to hold up to 8 splices each, this provides great comfort when working inside the enclosure, as the fibers are organized and spaced out.

Ref.	233004
Logical ref.	OSB48S-A
EAN13	8424450300817

Packaging info

Physical data

Box	1 pcs.	Net weight	2,500.00 g
		Gross weight	2,501.00 g
		Width	478.00 mm
		Height	180.00 mm
		Depth	151.00 mm
		Main product weight	2,500.00 g

Highlights

- Built in high-resistance ABS
- Easy service expansion: the enclosure is vertically stackable with similar boxes, making for a higher-capacity enclosure
- Comfortable working environment, thanks to the presence of trays on the left door, which allows working with the fibers on a horizontal surface
- Equipped with 6 independent folding FO trays (book format), with enough capacity to stow up to 8 splices each
- Equipped with 4 metal anchors to hold the main core elements, as provided by the FO cables
- Dust protection brush cable grommets at the top and bottom, for the passage of the interconnecting fiber to the enclosures or for operator access (up to 59x28 mm capacity)
- Equipped with 3 rubbers for 4 fiber accesses from the side
- Adhesive label on the door to identify each connector with the corresponding dwelling
- Dimensions (W x H x D): 478mm x 180mm x 151mm
- Grey colour (RAL 7035)

Technical specifications : Ref. 233004

Number of fibers		48
Number of inputs		3
Pre-cut openings		No
Independent compartments		Yes
Closure type		Door
Front door locking system		Key Lock, two-point lock
Type of connections		Connector and fusion splice
Installation type		Wall
Grounding		No
Material		ABS Plastic
Colour		Grey
Height	mm	180
Width	mm	450
Depth	mm	150