

Tekniska specifikationer : Ref. 60060000

Number of leds										12
Power	W									39
Pre-programmed dimming										No
Control interface										ON/OFF
Optic type options		P	T2	T3		ME		APZ	SCL	T4
Lens type		PC lens	PC lens	PC lens		PC lens		PC lens	PC lens	PC lens
Color temperature options		2200K		2700K		3000K		4000K		PC Amber
Luminous flux	lm	4426,5		4871,1		5382		5577		2281,5
Lighting efficiency	lm/W	113,5		124,9		138		143		58,5
LED current	mA	500		500		500		500		1000
Duration	h					100000				
Working life						L90B10				
Constant ligh output (CLO)						No				
Standard Deviation Colour Matching (SDCM)						< 3				
Color rendering index (CRI)						70				
CE Mark						Yes				
ENEC Certificate						No				
Protection Class IEC						Class II				
EU RoHS Compliant						Yes				
IK Rating (light module)						10				
IK Rating (whole luminaire)						10				
IP Rating (light module)						66				
IP Rating (whole luminaire)						66				
Colour						White/Grey				
Material						Technical Polymer				
Material cover						Without cover				
Fixation Material						Technical Polymer				
Mast diameter Max	mm					60				
Mast diameter Min	mm					42				
Mounting method						Post top/side entry				
Surface facing the wind	m²					0,1151				
Number of LED modules						1				
Minimum power factor						0.9500				
Lighting source type						LED				
Replaceable light source						Yes				
Cable						Yes				
Power consumption tolerance	%					5				
Lighting flux tolerance	%					8				
Electric connection						3-pole waterproof connector				
Inrush current	A					26				
Input voltage Max	Vac					240				
Input voltage Min	Vac					220				
Mains frequency						50 Hz				
Max. Operating temperature	°C					40				
Min. Operating temperature	°C					-35				