

Tekniska specifikationer : Ref. 60080000

Number of leds									12
Power	W								39
Pre-programmed dimming									No
Control interface									1-10V
Node/sensor connection type									1x ANSI C136.41 Nema
Optic type options									ME
Lens type		P	T2	T3		APZ	SCL	T4	
		PC lens	PC lens	PC lens	PC lens	PC lens	PC lens	PC lens	
Color temperature options		2200K		2700K		3000K		4000K	PC Amber
Luminous flux	lm	4540		4996		5520		5577	2340
Lighting efficiency	lm/W	113,5		124,9		138		143	58,5
LED current	mA	500		500		500		500	1000
Duration	h					100000			
Working life						L90B10			
Constant light output (CLO)						No			
Standard Deviation Colour Matching (SDCM)						< 3			
Color rendering index (CRI)						70			
CE Mark						Yes			
ENEC Certificate						No			
Protection Class IEC						Class II			
EU RoHS Compliant						Yes			
IK Rating (light module)						10			
IK Rating (whole luminaire)						9			
IP Rating (light module)						66			
IP Rating (whole luminaire)						66			
Colour						White/Grey			
Material						Technical Polymer			
Material cover						Without cover			
Fixation Material						Technical Polymer			
Mast diameter Max	mm					60			
Mast diameter Min	mm					42			
Mounting method						Post top/side entry			
Surface facing the wind	m²					0,1151			
Number of LED modules						1			
Minimum power factor						0.9500			
Lighting source type						LED			
Replaceable light source						Yes			
Cable						Yes			
Power consumption tolerance	%					5			
Lighting flux tolerance	%					8			
Electric connection						3-pole waterproof connector			
Inrush current	A					26			
Input voltage Max	Vac					240			
Input voltage Min	Vac					220			
Mains frequency						50 Hz			
Max. Operating temperature	°C					40			
Min. Operating temperature	°C					-35			