

Tekniska specifikationer : Ref. 60190200

Number of leds					24				
Power	W				70				
Pre-programmed dimming					Yes				
Control interface					Dali 2				
Node/sensor connection type					1x Zhaga				
Optic type options					ME				
Lens type		P	T2	T3	PC lens	APZ	SCL	T4	
Color temperature options		PC lens	PC lens	PC lens	PC lens	PC lens	PC lens	PC lens	
Luminous flux	lm	2200K	2700K	3000K	4000K	PC Amber			
Lighting efficiency	lm/W	7945	8743	9660	9940	4095			
LED current	mA	113,5	124,9	138	143	58,5			
Duration	h	450	450	450	450	900			
Working life					100000				
Constant light output (CLO)					L90B10				
Standard Deviation Colour Matching (SDCM)					Yes				
Color rendering index (CRI)					< 3				
CE Mark					70				
ENEC Certificate					Yes				
Protection Class IEC					No				
EU RoHS Compliant					Class II				
IK Rating (light module)					Yes				
IK Rating (whole luminaire)					10				
IP Rating (light module)					10				
IP Rating (whole luminaire)					66				
Colour					66				
Material					White/Grey				
Material cover					Technical Polymer				
Fixation Material					Without cover				
Mast diameter Max	mm				Technical Polymer				
Mast diameter Min	mm				60				
Mounting method					42				
Surface facing the wind	m²				Post top/side entry				
Number of LED modules					0,1151				
Minimum power factor					2				
Lighting source type					0.9500				
Replaceable light source					LED				
Cable					Yes				
Power consumption tolerance	%				Yes				
Lighting flux tolerance	%				5				
Electric connection					8				
Inrush current	A				3-pole waterproof connector				
Input voltage Max	Vac				54				
Input voltage Min	Vac				240				
Mains frequency					220				
Max. Operating temperature	°C				50 Hz				
Min. Operating temperature	°C				40				
					-35				