

Technical specifications : Ref. 62100000

Number of leds			252	
Power	W		150	
Pre-programmed dimming			No	
Control interface			1-10V	
Optic type options				
Color temperature options		3000K		4000K
Luminous flux	lm	19800		21435
Lighting efficiency	lm/W	132		142.9
LED current	mA	92		92
Duration	h		100000	
Working life			L70B10	
Constant high output (CLO)			No	
Standard Deviation Colour Matching (SDCM)			< 3	
Color rendering index (CRI)			80	
CE Mark			Yes	
ENEC Certificate			No	
Protection Class IEC			Class I	
EU RoHS Compliant			Yes	
IK Rating (light module)			8	
IK Rating (whole luminaire)			8	
IP Rating (light module)			66	
IP Rating (whole luminaire)			66	
Color			Black	
Material			Aluminium	
Fixation Material			Aluminium	
Mounting method			Suspended	
Surface facing the wind	m ²		2.77	
Number of LED modules			1	
Minimum power factor			0.9500	
Lighting source type			LED	
Replaceable light source			Yes	
Cable			Yes	
Power consumption tolerance	%		5	
Lighting flux tolerance	%		8	
Electric connection			3-pole waterproof connector	
Inrush current	A		50	
Input voltage Max	Vac		240	
Input voltage Min	Vac		220	
Mains frequency			50 Hz	
Total harmonic distortion (THD)			10	
Max. Operating temperature	°F		104	
Min. Operating temperature	°F		-31	