

Tekniska specifikationer : Ref. 62550000

Number of leds							72
Power	W						130
Pre-programmed dimming							No
Control interface							ON/OFF
Optic type options							S30
Lens type							S90
Color temperature options							S120
Luminous flux	lm						PC lens
Lighting efficiency	lm/W						PC lens
LED current	mA						3000K
Duration	h						4000K
Working life							PC Amber
Constant light output (CLO)							100000
Standard Deviation Colour Matching (SDCM)							L90B10
Color rendering index (CRI)							No
CE Mark							< 3
ENEC Certificate							70
Protection Class IEC							Yes
EU RoHS Compliant							No
IK Rating (light module)							Class I
IK Rating (whole luminaire)							Yes
IP Rating (light module)							10
IP Rating (whole luminaire)							10
Colour							66
Material							65
Fixation Material							Aluminum
Mounting method							Aluminium
Surface facing the wind	m ²						Suspended
Number of LED modules							0,13
Minimum power factor							6
Lighting source type							0,9500
Replaceable light source							LED
Cable							Yes
Power consumption tolerance	%						Yes
Lighting flux tolerance	%						Yes
Electric connection							3-pole waterproof connector
Inrush current	A						65
Input voltage Max	Vac						240
Input voltage Min	Vac						220
Mains frequency							50 Hz
Total harmonic distortion (THD)							20
Max. Operating temperature	°C						40
Min. Operating temperature	°C						-35