

Tekniska specifikationer : Ref. 63051100

Number of leds														12
Power	W													39
Pre-programmed dimming														No
Control interface														ON/OFF
Optic type options		P	SP	S30	S60	S90	T2	T3	ME	APZ	SCL	T4		
Lens type		PC lens	PC lens	PC lens	PC lens	PC lens	PC lens	PC lens	PC lens	PC lens	PC lens	PC lens		
Color temperature options			2200K		2700K		3000K		4000K				PC Amber	
Luminous flux	lm		4680		5070		5265		5850				2449,2	
Lighting efficiency	lm/W		120		130		135		150				62,8	
LED current	mA		325		325		325		325				650	
Duration	h						100000							
Working life							L90B10							
Constant ligh output (CLO)							No							
Standard Deviation Colour Matching (SDCM)							< 3							
Color rendering index (CRI)							70							
CE Mark							Yes							
ENEC Certificate							No							
Protection Class IEC							Class II							
EU RoHS Compliant							Yes							
IK Rating (light module)							10							
IK Rating (whole luminaire)							10							
IP Rating (light module)							68							
IP Rating (whole luminaire)							66							
Colour							Black							
Material							Technical Polymer							
Material cover							Without cover							
Fixation Material							Galvanized Steel							
Mounting method							Other							
Surface protection							Powder coating							
Number of LED modules							1							
Minimum power factor							0.9500							
Lighting source type							LED							
Replaceable light source							Yes							
Cable							Yes							
Power consumption tolerance	%						5							
Lighting flux tolerance	%						8							
Electric connection							3-pole waterproof connector							
Inrush current	A						26							
Input voltage Max	Vac						240							
Input voltage Min	Vac						220							
Mains frequency							50 Hz							
Max. Operating temperature	°C						40							
Min. Operating temperature	°C						-35							