

Tekniska specifikationer : Ref. 63071201

| | | | | | | | | | | | | |
|---|------|---------|---------|---------|---------|-----------------------------|---------|---------|---------|----------|--|-------|
| Number of leds | | | | | | | | | | | | 12 |
| Power | W | | | | | | | | | | | 39 |
| Pre-programmed dimming | | | | | | | | | | | | Yes |
| Control interface | | | | | | | | | | | | 1-10V |
| Optic type options | | P | SP | T2 | T3 | ME | APZ | SCL | T4 | | | |
| Lens type | | PC lens | PC lens | PC lens | PC lens | PC lens | PC lens | PC lens | PC lens | | | |
| Color temperature options | | 2200K | | 2700K | | 3000K | | 4000K | | PC Amber | | |
| Luminous flux | lm | 4095 | | 4485 | | 4680 | | 5120 | | 2028 | | |
| Lighting efficiency | lm/W | 105 | | 115 | | 120 | | 128 | | 52 | | |
| LED current | mA | 325 | | 325 | | 325 | | 325 | | 650 | | |
| Duration | h | | | | | 100000 | | | | | | |
| Working life | | | | | | L90B10 | | | | | | |
| Constant light output (CLO) | | | | | | No | | | | | | |
| Standard Deviation Colour Matching (SDCM) | | | | | | < 3 | | | | | | |
| Color rendering index (CRI) | | | | | | 70 | | | | | | |
| CE Mark | | | | | | Yes | | | | | | |
| ENEC Certificate | | | | | | No | | | | | | |
| Protection Class IEC | | | | | | Class II | | | | | | |
| EU RoHS Compliant | | | | | | Yes | | | | | | |
| IK Rating (light module) | | | | | | 10 | | | | | | |
| IK Rating (whole luminaire) | | | | | | 9 | | | | | | |
| IP Rating (light module) | | | | | | 68 | | | | | | |
| IP Rating (whole luminaire) | | | | | | 56 | | | | | | |
| Colour | | | | | | Black | | | | | | |
| Material | | | | | | Aluminium | | | | | | |
| Material cover | | | | | | Without cover | | | | | | |
| Fixation Material | | | | | | Aluminium | | | | | | |
| Mast diameter Max | mm | | | | | 60 | | | | | | |
| Mast diameter Min | mm | | | | | 42 | | | | | | |
| Mounting method | | | | | | Post top | | | | | | |
| Surface protection | | | | | | Powder coating | | | | | | |
| Surface facing the wind | m² | | | | | 0,3 | | | | | | |
| Number of LED modules | | | | | | 1 | | | | | | |
| Minimum power factor | | | | | | 0.9500 | | | | | | |
| Lighting source type | | | | | | LED | | | | | | |
| Replaceable light source | | | | | | Yes | | | | | | |
| Cable | | | | | | Yes | | | | | | |
| Power consumption tolerance | % | | | | | 5 | | | | | | |
| Lighting flux tolerance | % | | | | | 8 | | | | | | |
| Electric connection | | | | | | 3-pole waterproof connector | | | | | | |
| Inrush current | A | | | | | 26 | | | | | | |
| Input voltage Max | Vac | | | | | 240 | | | | | | |
| Input voltage Min | Vac | | | | | 220 | | | | | | |
| Mains frequency | | | | | | 50 Hz | | | | | | |
| Max. Operating temperature | °C | | | | | 40 | | | | | | |
| Min. Operating temperature | °C | | | | | -35 | | | | | | |