

Technical specifications : Ref. 63071400

Number of leds												12
Power	W											39
Pre-programmed dimming												No
Control interface												ON/OFF
Optic type options		P	T2	T3	ME	APZ	PX	SCL	T4			
Lens type		PC lens	PC lens	PC lens	PC lens	PC lens	PC lens	PC lens	PC lens			
Color temperature options		2200K		2700K		3000K		4000K		PC Amber		
Luminous flux	lm	4173		4563		4758		5070		1950		
Lighting efficiency	lm/W	107		117		122		130		50		
LED current	mA	500		500		500		500		1000		
Duration	h					100000						
Working life						L90B10						
Constant light output (CLO)						No						
Standard Deviation Colour Matching (SDCM)						< 3						
Color rendering index (CRI)						70						
CE Mark						Yes						
ENEC Certificate						No						
Protection Class IEC						Class II						
EU RoHS Compliant						Yes						
IK Rating (light module)						8						
IK Rating (whole luminaire)						8						
IP Rating (light module)						66						
IP Rating (whole luminaire)						66						
Color						Black						
Material						Aluminium						
Material cover						Transparent plastic						
Fixation Material						Aluminium						
Mast diameter Max	in					2.362						
Mast diameter Min	in					1.654						
Mounting method						Post top/side entry						
Surface protection						Powder coating						
Surface facing the wind	m²					0.211						
Number of LED modules						1						
Minimum power factor						0.9500						
Lighting source type						LED						
Replaceable light source						Yes						
Cable						Yes						
Power consumption tolerance	%					5						
Lighting flux tolerance	%					8						
Electric connection						3-pole waterproof connector						
Inrush current	A					26						
Input voltage Max	Vac					240						
Input voltage Min	Vac					220						
Mains frequency						50 Hz						
Max. Operating temperature	°F					104						
Min. Operating temperature	°F					-31						