

Tekniska specifikationer : Ref. 63071401

Number of leds												12
Power	W											39
Pre-programmed dimming												Yes
Control interface												1-10V
Optic type options		P	T2	T3	ME	APZ	PX	SCL	T4			
Lens type		PC lens	PC lens	PC lens	PC lens	PC lens	PMMA lens	PC lens	PC lens			
Color temperature options		2200K		2700K		3000K		4000K			PC Amber	
Luminous flux	lm	4173		4563		4758		5070			1950	
Lighting efficiency	lm/W	107		117		122		130			50	
LED current	mA	500		500		500		500			1000	
Duration	h					100000						
Working life						L90B10						
Constant light output (CLO)						No						
Standard Deviation Colour Matching (SDCM)						< 3						
Color rendering index (CRI)						70						
CE Mark						Yes						
ENEC Certificate						No						
Protection Class IEC						Class II						
EU RoHS Compliant						Yes						
IK Rating (light module)						8						
IK Rating (whole luminaire)						8						
IP Rating (light module)						66						
IP Rating (whole luminaire)						66						
Colour						Black						
Material						Aluminium						
Material cover						Transparent plastic						
Fixation Material						Aluminium						
Mast diameter Max	mm					60						
Mast diameter Min	mm					42						
Mounting method						Post top/side entry						
Surface protection						Powder coating						
Surface facing the wind	m²					0,2112						
Number of LED modules						1						
Minimum power factor						0.9500						
Lighting source type						LED						
Replaceable light source						Yes						
Cable						Yes						
Power consumption tolerance	%					5						
Lighting flux tolerance	%					8						
Electric connection						3-pole waterproof connector						
Inrush current	A					26						
Input voltage Max	Vac					240						
Input voltage Min	Vac					220						
Mains frequency						50 Hz						
Max. Operating temperature	°C					40						
Min. Operating temperature	°C					-35						