

## Tekniska specifikationer : Ref. 63150000

Number of leds															24
Power	W														53
Pre-programmed dimming															No
Control interface															ON/OFF
Optic type options		P	SP	S30	S60	S90	T2	T3	ME	APZ	SCL	T4			
Lens type		PC lens	PC lens	PC lens	PC lens	PC lens	PC lens	PC lens	PC lens	PC lens	PC lens	PC lens	PC lens		
Color temperature options			2200K		2700K		3000K		4000K				PC Amber		
Luminous flux	lm		6360		6890		7155		7950				3328,4		
Lighting efficiency	lm/W		120		130		135		150				62,8		
LED current	mA		325		325		325		325				650		
Duration	h						100000								
Working life							L90B10								
Constant light output (CLO)							No								
Standard Deviation Colour Matching (SDCM)							< 3								
Color rendering index (CRI)							70								
CE Mark							Yes								
ENEC Certificate							No								
Protection Class IEC							Class II								
EU RoHS Compliant							Yes								
IK Rating (light module)							10								
IK Rating (whole luminaire)							10								
IP Rating (light module)							68								
IP Rating (whole luminaire)							66								
Colour							Black								
Material							Technical Polymer								
Material cover							Without cover								
Fixation Material							Galvanized Steel								
Mounting method							Other								
Surface protection							Powder coating								
Number of LED modules							2								
Minimum power factor							0.9500								
Lighting source type							LED								
Replaceable light source							Yes								
Cable							Yes								
Power consumption tolerance	%						5								
Lighting flux tolerance	%						8								
Electric connection							3-pole waterproof connector								
Inrush current	A						54								
Input voltage Max	Vac						240								
Input voltage Min	Vac						220								
Mains frequency							50 Hz								
Max. Operating temperature	°C						40								
Min. Operating temperature	°C						-35								