

Tekniska specifikationer : Ref. 63030001

Number of leds												12
Power	W											39
Pre-programmed dimming												Yes
Control interface												1-10V
Optic type options		P	SP	T2	T3	ME	APZ	SCL	T4			
Lens type		PC lens	PC lens	PC lens	PC lens	PC lens	PC lens	PC lens	PC lens			
Color temperature options		2200K		2700K		3000K		4000K		PC Amber		
Luminous flux	lm	3744		3900		3989,7		4290		1950		
Lighting efficiency	lm/W	96		100		102,3		110		50		
LED current	mA	500		500		500		500		1000		
Duration	h					100000						
Working life						L90B10						
Constant light output (CLO)						No						
Standard Deviation Colour Matching (SDCM)						< 3						
Color rendering index (CRI)						70						
CE Mark						Yes						
ENEC Certificate						No						
Protection Class IEC						Class II						
EU RoHS Compliant						Yes						
IK Rating (light module)						8						
IK Rating (whole luminaire)						8						
IP Rating (light module)						66						
IP Rating (whole luminaire)						56						
Colour						Inox						
Material						stainless steel						
Material cover						Without cover						
Fixation Material						Stainless Steel						
Mounting method						Wall bracket						
Surface protection						Lacquered						
Surface facing the wind	m ²					0,113						
Number of LED modules						1						
Minimum power factor						0.9500						
Lighting source type						LED						
Replaceable light source						Yes						
Cable						Yes						
Power consumption tolerance	%					5						
Lighting flux tolerance	%					8						
Electric connection						3-pole waterproof connector						
Inrush current	A					26						
Input voltage Max	Vac					240						
Input voltage Min	Vac					220						
Mains frequency						50 Hz						
Max. Operating temperature	°C					40						
Min. Operating temperature	°C					-35						