

Technical specifications : Ref. 63170100

| | | | | | | | | | | |
|---|------|---------|---------|---------|---------|---------|---------|---------|----------|-----------------------------|
| Number of leds | | | | | | | | | | 24 |
| Power | W | | | | | | | | | 53 |
| Pre-programmed dimming | | | | | | | | | | No |
| Control interface | | | | | | | | | | ON/OFF |
| Optic type options | | P | SP | T2 | T3 | ME | APZ | SCL | T4 | |
| Lens type | | PC lens | PC lens | PC lens | PC lens | PC lens | PC lens | PC lens | PC lens | |
| Color temperature options | | 2200K | | 2700K | | 3000K | | 4000K | PC Amber | |
| Luminous flux | lm | 5618 | | 6148 | | 6413 | | 6837 | 2809 | |
| Lighting efficiency | lm/W | 106 | | 116 | | 121 | | 129 | 53 | |
| LED current | mA | 325 | | 325 | | 325 | | 325 | 650 | |
| Duration | h | | | | | | | | | 100000 |
| Working life | | | | | | | | | | L90B10 |
| Constant light output (CLO) | | | | | | | | | | No |
| Standard Deviation Colour Matching (SDCM) | | | | | | | | | | < 3 |
| Color rendering index (CRI) | | | | | | | | | | 70 |
| CE Mark | | | | | | | | | | Yes |
| ENEC Certificate | | | | | | | | | | No |
| Protection Class IEC | | | | | | | | | | Class II |
| EU RoHS Compliant | | | | | | | | | | Yes |
| IK Rating (light module) | | | | | | | | | | 10 |
| IK Rating (whole luminaire) | | | | | | | | | | 9 |
| IP Rating (light module) | | | | | | | | | | 68 |
| IP Rating (whole luminaire) | | | | | | | | | | 56 |
| Color | | | | | | | | | | Black |
| Material | | | | | | | | | | Aluminium |
| Material cover | | | | | | | | | | Without cover |
| Fixation Material | | | | | | | | | | Aluminium |
| Mast diameter Max | in | | | | | | | | | 2.362 |
| Mast diameter Min | in | | | | | | | | | 1.654 |
| Mounting method | | | | | | | | | | Post top |
| Surface protection | | | | | | | | | | Powder coating |
| Surface facing the wind | m² | | | | | | | | | 0.16 |
| Number of LED modules | | | | | | | | | | 2 |
| Minimum power factor | | | | | | | | | | 0.9500 |
| Lighting source type | | | | | | | | | | LED |
| Replaceable light source | | | | | | | | | | Yes |
| Cable | | | | | | | | | | Yes |
| Power consumption tolerance | % | | | | | | | | | 5 |
| Lighting flux tolerance | % | | | | | | | | | 8 |
| Electric connection | | | | | | | | | | 3-pole waterproof connector |
| Inrush current | A | | | | | | | | | 54 |
| Input voltage Max | Vac | | | | | | | | | 240 |
| Input voltage Min | Vac | | | | | | | | | 220 |
| Mains frequency | | | | | | | | | | 50 Hz |
| Max. Operating temperature | °F | | | | | | | | | 104 |
| Min. Operating temperature | °F | | | | | | | | | -31 |