

## Technical specifications : Ref. 63170200

Number of leds										24
Power	W									53
Pre-programmed dimming										No
Control interface										ON/OFF
Optic type options		P	SP	T2	T3	ME	APZ	SCL	T4	
Lens type		PC lens	PC lens	PC lens	PC lens	PC lens	PC lens	PC lens	PC lens	
Color temperature options		2200K		2700K		3000K		4000K	PC Amber	
Luminous flux	lm	5565		6095		6360		6784	2756	
Lighting efficiency	lm/W	105		115		120		128	52	
LED current	mA	325		325		325		325	650	
Duration	h									100000
Working life										L90B10
Constant light output (CLO)										No
Standard Deviation Colour Matching (SDCM)										< 3
Color rendering index (CRI)										70
CE Mark										Yes
ENEC Certificate										No
Protection Class IEC										Class II
EU RoHS Compliant										Yes
IK Rating (light module)										10
IK Rating (whole luminaire)										9
IP Rating (light module)										68
IP Rating (whole luminaire)										56
Color										Black
Material										Aluminium
Material cover										Without cover
Fixation Material										Aluminium
Mast diameter Max	in									2.362
Mast diameter Min	in									1.654
Mounting method										Post top
Surface protection										Powder coating
Surface facing the wind	m²									0.3
Number of LED modules										2
Minimum power factor										0.9500
Lighting source type										LED
Replaceable light source										Yes
Cable										Yes
Power consumption tolerance	%									5
Lighting flux tolerance	%									8
Electric connection										3-pole waterproof connector
Inrush current	A									54
Input voltage Max	Vac									240
Input voltage Min	Vac									220
Mains frequency										50 Hz
Max. Operating temperature	°F									104
Min. Operating temperature	°F									-31