Televes®

Tekniska specifikationer : Ref. 63550000

Number of leds		72										
Power	W	195										
Pre-programmed dimming		No										
Control interface		ON/OFF										
Optic type options		P	SP	S30	S60	S90	T2	T3	ME	APZ	SCL	T4
Lens type		PC lens	PC lens	PC lens	PC lens	PC lens	PC lens	PC lens	PC lens	PC lens	PC lens	PC lens
Color temperature options		2200K		2700K		3000K			4000K		PC Amber	
Luminous flux	lm	23400		25350		26325			29250		12246	
Lighting efficiency	lm/W	120		130		135			150		62,8	
LED current	mA	325		325		325			325		650	
Duration	h	100000										
Working life		L90B10										
Constant ligh output (CLO)		Yes										
Standard Deviation Colour Matching (SDCM)		< 3										
Color rendering index (CRI)		70										
CE Mark		Yes										
ENEC Certificate		No										
Protection Class IEC		Class II										
EU RoHS Compliant		Yes										
IK Rating (light module)		10										
IK Rating (whole luminaire)		10										
IP Rating (light module)		68										
IP Rating (whole luminaire)		66										
Colour		Black										
Material		Aluminium										
Material cover		Without cover										
Fixation Material		Aluminium										
Mounting method		Other										
Surface protection		Powder coating										
Number of LED modules		6										
Minimum power factor		0.9500										
Lighting source type		LED										
Replaceable light source		Yes										
Cable		Yes										
Power consumption tolerance	%	5										
Lighting flux tolerance	%	8										
Electric connection		3-pole waterproof connector										
Inrush current	A	54										
Input voltage Max	Vac	240										
Input voltage Min	Vac	220										
Mains frequency		50 Hz										
Max. Operating temperature	°C	40										
Min. Operating temperature	°C	-35										