

Tekniska specifikationer : Ref. 66071400

Number of leds											12
Power	W										40
Pre-programmed dimming											Yes
Control interface											Dali 2
Optic type options		P	T2	T3	ME	APZ	PX	SCL	T4		
Lens type		PC lens	PC lens	PC lens	PC lens	PC lens	PMMA lens	PC lens	PC lens		
Color temperature options		2200K		2700K		3000K		4000K		PC Amber	
Luminous flux	lm	4280		4680		4880		5200		2000	
Lighting efficiency	lm/W	107		117		122		130		50	
LED current	mA	500		500		500		500		1000	
Duration	h					100000					
Working life						L90B10					
Constant light output (CLO)						Yes					
Standard Deviation Colour Matching (SDCM)						< 3					
Color rendering index (CRI)						70					
CE Mark						Yes					
ENEC Certificate						No					
Protection Class IEC						Class II					
EU RoHS Compliant						Yes					
IK Rating (light module)						8					
IK Rating (whole luminaire)						8					
IP Rating (light module)						66					
IP Rating (whole luminaire)						66					
Colour						Black					
Material						Aluminium					
Material cover						Transparent plastic					
Fixation Material						Aluminium					
Mast diameter Max	mm					60					
Mast diameter Min	mm					42					
Mounting method						Post top/side entry					
Surface protection						Powder coating					
Surface facing the wind	m²					0,2112					
Number of LED modules						1					
Minimum power factor						0.9500					
Lighting source type						LED					
Replaceable light source						Yes					
Cable						Yes					
Power consumption tolerance	%					5					
Lighting flux tolerance	%					8					
Electric connection						3-pole waterproof connector					
Inrush current	A					26					
Input voltage Max	Vac					240					
Input voltage Min	Vac					220					
Mains frequency						50 Hz					
Max. Operating temperature	°C					40					
Min. Operating temperature	°C					-35					