

Tekniska specifikationer : Ref. 66190300

| | | | | | |
|---|----------------|---------|-----------|-----------|-----------------------------|
| Number of leds | | | | | 24 |
| Power | W | | | | 60 |
| Pre-programmed dimming | | | | | Yes |
| Control interface | | | | | Dali 2 |
| Node/sensor connection type | | | | | 1x Zhaga |
| Optic type options | | SP | D90 | T2C90 | T3B90 |
| Lens type | | PC lens | PMMA lens | PMMA lens | PMMA lens |
| Color temperature options | | 2200K | 2700K | 3000K | 4000K |
| Luminous flux | lm | 6300 | 6900 | 7200 | 7680 |
| Lighting efficiency | lm/W | 105 | 115 | 120 | 128 |
| LED current | mA | 325 | 325 | 325 | 325 |
| Duration | h | | | | 650 |
| Working life | | | | | 100000 |
| Constant light output (CLO) | | | | | L90B10 |
| Standard Deviation Colour Matching (SDCM) | | | | | Yes |
| Color rendering index (CRI) | | | | | < 3 |
| CE Mark | | | | | 70 |
| ENEC Certificate | | | | | Yes |
| Protection Class IEC | | | | | No |
| EU RoHS Compliant | | | | | Class II |
| IK Rating (light module) | | | | | Yes |
| IK Rating (whole luminaire) | | | | | 8 |
| IP Rating (light module) | | | | | 8 |
| IP Rating (whole luminaire) | | | | | 66 |
| Colour | | | | | 66 |
| Material | | | | | Black |
| Material cover | | | | | Aluminium |
| Fixation Material | | | | | Transparent plastic |
| Mast diameter Max | mm | | | | Aluminium |
| Mast diameter Min | mm | | | | 80 |
| Mounting method | | | | | 42 |
| Surface protection | | | | | Post top |
| Surface facing the wind | m ² | | | | Powder coating |
| Number of LED modules | | | | | 0,2112 |
| Minimum power factor | | | | | 2 |
| Lighting source type | | | | | 0.9500 |
| Replaceable light source | | | | | LED |
| Cable | | | | | Yes |
| Power consumption tolerance | % | | | | Yes |
| Lighting flux tolerance | % | | | | 5 |
| Electric connection | | | | | 8 |
| Inrush current | A | | | | 3-pole waterproof connector |
| Input voltage Max | Vac | | | | 54 |
| Input voltage Min | Vac | | | | 240 |
| Mains frequency | | | | | 220 |
| Max. Operating temperature | °C | | | | 50 Hz |
| Min. Operating temperature | °C | | | | 40 |
| | | | | | -35 |