

## Technical specifications : Ref. 67100000

Number of leds					24
Power	W				58
Pre-programmed dimming					No
Control interface					ON/OFF
Optic type options		S30	S60	S90	APZ
Lens type		PC lens	PC lens	PC lens	PC lens
Color temperature options		2200K	2700K	3000K	4000K
Luminous flux	lm	6960	7540	7830	8700
Lighting efficiency	lm/W	120	130	135	150
LED current	mA	375	375	375	375
Duration	h				100000
Working life					L90B10
Constant light output (CLO)					No
Standard Deviation Colour Matching (SDCM)					< 3
Color rendering index (CRI)					70
CE Mark					Yes
ENEC Certificate					No
Protection Class IEC					Class II
EU RoHS Compliant					Yes
IK Rating (light module)					10
IK Rating (whole luminaire)					10
IP Rating (light module)					66
IP Rating (whole luminaire)					66
Color					Aluminium
Material					Aluminium
Material cover					Without cover
Fixation Material					Aluminium
Mounting method (Floodlights)					Wall / Traverse / Pedestal/Floor
Surface protection					Anodized
Surface facing the wind	m <sup>2</sup>				0.084
Number of LED modules					2
Minimum power factor					0.9500
Lighting source type					LED
Replaceable light source					Yes
Cable					Yes
Power consumption tolerance	%				5
Lighting flux tolerance	%				8
Electric connection					3-pole waterproof connector
Inrush current	A				54
Input voltage Max	Vac				240
Input voltage Min	Vac				220
Mains frequency					50 Hz
Total harmonic distortion (THD)					20
Max. Operating temperature	°F				104
Min. Operating temperature	°F				-31