

Technical specifications : Ref. 67100001

Number of leds						24
Power	W					58
Pre-programmed dimming						Yes
Control interface						1-10V
Optic type options		S30	S60	S90	APZ	
Lens type		PC lens	PC lens	PC lens	PC lens	
Color temperature options		2200K	2700K	3000K	4000K	PC Amber
Luminous flux	lm	6960	7540	7830	8700	3596
Lighting efficiency	lm/W	120	130	135	150	62
LED current	mA	375	375	375	375	750
Duration	h					100000
Working life						L90B10
Constant light output (CLO)						No
Standard Deviation Colour Matching (SDCM)						< 3
Color rendering index (CRI)						70
CE Mark						Yes
ENEC Certificate						No
Protection Class IEC						Class II
EU RoHS Compliant						Yes
IK Rating (light module)						10
IK Rating (whole luminaire)						10
IP Rating (light module)						66
IP Rating (whole luminaire)						66
Color						Aluminium
Material						Aluminium
Material cover						Without cover
Fixation Material						Aluminium
Mounting method (Floodlights)						Wall / Traverse / Pedestal/Floor
Surface protection						Anodized
Surface facing the wind	m ²					0.084
Number of LED modules						2
Minimum power factor						0.9500
Lighting source type						LED
Replaceable light source						Yes
Cable						Yes
Power consumption tolerance	%					5
Lighting flux tolerance	%					8
Electric connection						3-pole waterproof connector
Inrush current	A					54
Input voltage Max	Vac					240
Input voltage Min	Vac					220
Mains frequency						50 Hz
Total harmonic distortion (THD)						20
Max. Operating temperature	°F					104
Min. Operating temperature	°F					-31